

Foundry Hook FH POWERTEX

Product information



The POWERTEX Foundry Hook FH is designed for the assembly of chain slings where wide throat openings are necessary. It is part of the Powertex G10 Lifting Sling Chain Components range.

Available for chain size 6 mm up to 16 mm and WLL 1.4t up to 10t.

Powerdex G10 Range benefits:

- 25% higher capacity compared to traditional Grade 8 components
- All POWERTEX G10 components are powder painted in luminous red
- Multi-functional master links and components are included in the range to allow quick and cost-effective assembly of chain slings
- The components meet EN 1677 part 1/2/3/4 +25% WLL
- Each forged component is crack detection tested, and samples are proof load tested.
- Each component is type tested in the factory and fatigue rated to 20,000 cycles at 1.5 times the WLL
- Full traceability through a batch number
- Replacement spare parts available
- All components are chromium 6 free
- POWERTEX 2.2 certificate enclosed with each box of components
- The components may also be used with Grade 8 chain to EN 818-2. In such a case, the chain sling needs to be rated as Grade 8 in accordance with EN 818-2 ... [Read more](#)

Marking: According to standard


Standard: EN 1677-1 (+ 25% WLL), AS 3776

Safety factor: 4:1

Класс: 10

Foundry Hook FH POWERTEX

Blueprint



Technical data

Код товара	Код	Chain diameter mm	WLL ton	EWL mm	E mm	H mm	L mm	M mm	Ø mm mm	Ø1 mm	Вес kg
402300141480	FH-6-10	6	1,4	114	49	17	133	19	20	10	0,4
402300251480	FH-8-10	8	2,5	130	62	19	157	27	24	12	0,7
402300401480	FH-10-10	10	4	169	73	25	199	30	31,5	15	1,4
402300671480	FH-13-10	13	6,7	199	90	33	238	39	44	19	2,6
402301001480	FH-16-10	16	10	237	105	42	279	42	49	22	4