

Master Link M POWERTEX

Product information



The POWERTEX Master Link M is part of the range of Powertex G10 Lifting Sling Chain Components. Master Link M is to be used as the top ring one-leg and two-legged chain sling assemblies.

Available for 6 mm up to 32 mm chain and from WLL 1.4t up to WLL 56t. All models up to M-3226-10 are forged. Model M-3632-10 is welded.

Powerdex G10 Range benefits:

- 25% higher capacity compared to traditional Grade 8 components
- All POWERTEX G10 components are powder painted in luminous red
- Multi-functional master links and components are included in the range to allow quick and cost-effective assembly of chain slings
- The components meet EN 1677 part 1/2/3/4 +25% WLL
- Each forged component is crack detection tested, and samples are proof load tested.
- Each component is type tested in the factory and fatigue rated to 20,000 cycles at 1.5 times the WLL
- Full traceability through a batch number
- Replacement spare parts available
- All components are chromium 6 free
- POWERTEX 2.2 certificate enclosed with each box of components
- The components may also be used with Grade 8 chain to EN 818-2. In such a case, the chain sling needs to be rated as Grade 8 in accordance with EN 818-2 ... [Read more](#)

Marking: According to standard


Standard: EN 1677-4 (+25% WLL) , AS 3776

Safety factor: 4:1

Класс: 10

Master Link M POWERTEX

Blueprint



Technical data

Код товара	Код	WLL ton	EWL mm	For chain, 1-leg mm	For chain, 2-leg mm	A mm	B mm	H mm	S mm	Ø mm mm	Bec kg
402100140750	M-6-10	1,4	100	6	-	100	60	28	6	11	0,23
402100250750	M-86-10	2,5	120	8	6	120	70	28	7	13	0,4
402100400750	M-108-10	4	140	10	8	140	80	28	8	17	0,7
402100670750	M-1310-10	6,7	160	13	10	160	95	43	11	22	1,5
402101000750	M-1613-10	10	190	16	13	190	110	43	13	27	2,6
402101600750	M-2016-10	16	240	20	16	240	140	60	17	32	5,1
402102240750	M-2220-10	22,4	250	22	20	250	150	60	21	38	7,2
402102650750	M-2622-10	26,5	250	26	22	250	150	60	23	40	7,8
402104000750	M-3226-10	40	300	32	26	300	180	64	27	50	14,8
402105600750	M-3632-10	56	400	36	32	400	200	-	-	60	27