

Lifting Eye Bolt RUD RS, UNC/UN thread

Product information



- considerably higher WLL in comparison to DIN 580
- clear marking of the minimum WLL
- comprehensive range of threads

... [Read more](#)


Marking: According to standard

Standard: EN 1677-1

Safety factor: 4:1

Lifting Eye Bolt RUD RS, UNC/UN thread

Blueprint



Technical data

| Код товара | WLL ton | Thread Inch | A mm | B mm | C mm | D mm | E mm | T mm | Bec kg |
|--------------|---------|-------------|------|------|------|------|------|------|--------|
| 421100010722 | 0,1 | 1/4 -20 | 12 | 11 | 10 | 25 | 25 | 34 | 0,1 |
| 421100020720 | 0,2 | 5/16 -18 | 12 | 11 | 10 | 25 | 25 | 34 | 0,1 |
| 421102500720 | 0,25 | 3/8 -16 | 15 | 11 | 10 | 25 | 25 | 34 | 0,1 |
| 421104000720 | 0,4 | 7/16 -14 | 18 | 13 | 12 | 30 | 30 | 41 | 0,18 |
| 421104000725 | 0,4 | 1/2 -13 | 18 | 13 | 12 | 30 | 30 | 41 | 0,18 |
| 421107500720 | 0,75 | 9/16 -12 | 22 | 15 | 14 | 35 | 35 | 48 | 0,3 |
| 421100100720 | 1 | 5/8 -11 | 24 | 15 | 14 | 35 | 35 | 48 | 0,3 |
| 421100120720 | 1,2 | 3/4 -10 | 30 | 17 | 16 | 40 | 40 | 55 | 0,47 |
| 421100150720 | 1,5 | 7/8 -9 | 34 | 21 | 20 | 50 | 50 | 70 | 0,8 |
| 421100200720 | 2 | 1 -8 | 36 | 21 | 20 | 50 | 50 | 70 | 0,85 |
| 421100250720 | 2,5 | 1 1/8 -7 | 45 | 26 | 24 | 60 | 60 | 85 | 1,6 |
| 421100250725 | 2,5 | 1 1/8 -8 | 45 | 26 | 24 | 60 | 60 | 85 | 1,6 |
| 421100300720 | 3 | 1 1/4 -7 | 46 | 26 | 24 | 60 | 60 | 85 | 1,6 |
| 421100300725 | 3 | 1 1/4 -8 | 45 | 26 | 24 | 60 | 60 | 85 | 1,6 |
| 421100300726 | 3 | 1 3/8 -6 | 55 | 43 | 38 | 90 | 100 | 130 | 6,1 |
| 421100400720 | 4 | 1 1/2 -6 | 58 | 43 | 38 | 90 | 100 | 130 | 6,2 |
| 421100400725 | 4 | 1 1/2 -8 | 58 | 43 | 38 | 90 | 100 | 130 | 6,5 |
| 421100600720 | 6 | 1 3/4 -5 | 67 | 43 | 38 | 90 | 100 | 130 | 6,3 |
| 421100600725 | 6 | 1 3/4 -8 | 67 | 43 | 38 | 90 | 100 | 130 | 6,5 |
| 421100800720 | 8 | 2 -4.5 | 67 | 43 | 38 | 90 | 100 | 130 | 6,5 |