



Lifting Eye RUD VLBG-Z, UNC thread

Product information

- Captive but exchangeable RUD-Bolt
- Bracket adjustable in force direction
- Comprehensive range of threads

Marking: According to standard

Standard: EN 1677-1

Safety factor: 4:1

Код товара	WLL ton	Thread Inch	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	K mm	L mm	N mm	T mm	Bec kg
42158504256	0,63	3/8 -16	30	54	34	24	39	10	29	16	75	45	45	32	75	0,29
42158502349	1	1/2 -13	32	54	34	26	38	10	29	22	75	45	50	32	75	0,36
42158502350	1,5	5/8 -11	33	56	36	30	39	13,5	36	24	86	47	60	38	85	0,5
42158502352	2,5	7/8 -9	50	82	54	45	55	16,5	43	27	113	64	70	48	110	1,25
42158502351	2,5	3/4 -10	50	82	54	45	55	16,5	43	28	113	64	71	48	110	1,3
42158502353	4	1 -8	50	82	54	45	67	18	43	41	130	78	84	48	125	1,5
42158504257	8	1 1/2 -6	77	122	82	70	97	26,5	77	62	205	110	140	87	197	6,14

Blueprint

