



Lifting Eye RUD VRS-F Starpoint, UNC thread

Product information

- 360° adjustable in force direction
- several times higher WLL than the DIN 580 eye bolt
- Easy-Fit-Key for easy assembly and disassembly

Marking: CE-marked

Safety factor: 4:1

Код товара	WLL ton	Thread Inch	B mm	C mm	D mm	E mm	G mm	I mm	K mm	L	N mm	T mm	Вес kg
421100030740	0,3	5/16-18	11	9	25	25	30	16,3	47	12	7,94	35	0,13
421100040740	0,4	3/8 -16	11	9	25	25	30	16,3	47	15	6,35	35	0,12
421100040745	0,4	7/16 -14	11	9	25	25	30	16,3	47	15	6,35	35	0,12
421100080740	0,75	1/2 -13	13	10	30	30	34	19,8	56	19	7,94	42	0,22
421100150740	1,5	5/8 -11	15	13	35	36	40	23,5	65	24	9,53	49	0,33
421100230740	2,3	3/4 -10	17	16	40	41	50	29,3	76	29	12,7	58	0,58
421100230745	2,3	7/8 -9	17	16	40	41	50	29,3	76	33	12,7	58	0,61
421100320740	3,2	1 -8	20	19	49	51	60	35	92	36	14,29	70	0,98
421100320745	3,2	1-1/8"-7	20	19	49	51	60	35	92	36	9/16"	70	1
421100320746	3,2	1-1/8"-8	20	19	49	51	60	35	92	36	9/16"	70	1
421100450740	4,5	1 1/4 -7	26	24	60	66	75	44	114	48	15,88	87	2,08
421100700740	7	1 1/2 -6	32	29	73	76	98	53	135	54	22,23	104	3,6
421100900740	9	1 3/4 -5	37	33	84	86	111	62	158	63	25,4	121	4,95
421101200740	12	2 -4.5	42	42	94	100	128	70	180	72	28,58	138	7,6

Blueprint

