

Lifting Point RUD B-ABA

Product information



The RUD B-ABA ring is a lifting point designed for handling heavy loads in all loading directions.

Product features:

- 100% of the WLL in all directions, without any reduction
- No rattling or play, even under strong vibrations or shock loads
- Wear indicators on the inside and outside of the body


... [Read more](#)

Marking: According to standard
Standard: EN 1677-1, EN ISO 12100

Safety factor: 4:1

Lifting Point RUD B-ABA

Blueprint



Technical data

| Код товара | WLL ton | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | L mm | M mm | T mm | Вес kg |
|-------------|---------|------|------|------|------|------|------|------|------|------|------|------|--------|
| 42157906266 | 1,6 | 75 | 16 | 100 | 35 | 16 | 62,5 | 55 | 55 | 13 | M10 | 47 | 0,88 |
| 42157906267 | 3,2 | 92 | 23 | 137 | 50 | 21 | 86 | 70 | 75 | 16 | M12 | 65 | 2,01 |
| 42157906268 | 5 | 113 | 27 | 172 | 60 | 28 | 108 | 84 | 95 | 24 | M16 | 80 | 4,07 |
| 42157906269 | 10 | 146 | 38 | 228 | 80 | 36 | 141 | 110 | 125 | 25 | M20 | 105 | 9,31 |
| 42157906270 | 20 | 200 | 52 | 272 | 115 | 40 | 188 | 150 | 75 | 30 | M24 | 148 | 18,77 |
| 42157906271 | 31,5 | 230 | 64 | 320 | 130 | 50 | 220 | 175 | 87,5 | 40 | M30 | 170 | 29,5 |