

Wire rope Dyform Bristar 8

Product information



Dyform Bristar 8 is a high performance compacted single layer constructed rope which incorporates an engineered extruded plastic profile between the 8 outer strands and the rope core for cranes and industrial applications including mobile, crawler and tower cranes.

Standard: EN 12385-4

ISO 4309 Rope Category No: 10-17mm **RCN.04**, 18-34mm **RCN.09**, 36-50mm **RCN.11**

... [Read more](#)

Marking: According to standard

Standard: EN 12385-4

Fill factor: 0.68

RCN: 04

Wire rope Dyform Bristar 8

Technical data

Код товара	Rope diameter mm	Tensile strength N/mm ²	Finish	Rope lay	Min. breaking force kN	Steel area mm ²	Lubrication	Bec kg/100m
103102804270659	28	1 960	Galvanized	sZ	691	-	SupplierStandard	367
103103203270709	32	1 960	Galvanized	zS	903	-	SupplierStandard	482
103103404270709	34	1 960	Galvanized	sZ	1 020	-	SupplierStandard	544
103103604270709	36	1 960	Galvanized	sZ	1 145	-	SupplierStandard	613
103103603270709	36	1 960	Galvanized	zS	1 145	-	SupplierStandard	613
103103804270709	38	1 960	Galvanized	sZ	1 300	-	SupplierStandard	685
103103803270709	38	1 960	Galvanized	zS	1 300	-	SupplierStandard	685