Lifting Solutions Group
Axel Johnson International

Ferrule TKH Talurit®

Product information



The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. The ferrules are thoroughly specified and very well defined for many different wire rope applications.

Conical ferrule with an inspection hole to ensure the short end of the wire rope is correctly positioned after swaging. This hole remains open after swaging, due to the pressing in a die with a blind tap.

The ferrules can be used for fibre core, single layer wire ropes, steel core single layer wire ropes, rotation resistant wire ropes and some spiral strand ropes.

... *Read more*

Marking: According to standard
Standard: EN 13411-3
except size range

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Ferrule TKH Talurit®

Technical data

Код товара	Ferrule size mm
120100800200	8
120100900200	9
120101000200	10
120101100200	11
120101200200	12
120101300200	13
120101400200	14
120101600200	16
120101800200	18
120102000200	20
120102200200	22
120102400200	24
120102600200	26
120102800200	28
120103000200	30
120103200200	32
120103400200	34
120103600200	36
120103800200	38
120104000200	40
120104400200	44
120105000200	50
120105400200	54
120104200200	42
120100700200	7
120100650200	6,5
120104800200	48
120105200200	52
120105600200	56
120105800200	58
120106000200	60

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Ferrule TKH Talurit®

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved