

Hydraulic Hoses - Standard Hoses - H SOU

Product information



Holmatro Standard hoses

- Suitable for high pressure hydraulics / max 700bar working pressure
- Anti-kink spring on both sides
- All hoses are individually tested during the production proces.
- Safety factor 4:1
- 6 year max. lifespan.

Standard supplied with:

- Hose connection A = 3/8" NPT male
- Hose connection B = A 119 male coupler
- Already filled with oil.

Also available:

- Hydraulic cylinders
- Hydraulic pump units 700bar to control the cylinder(s)
- System components to complete your hydraulic system

Available on request:

- Different lengths.
- Other colour.

... [Read more](#)

Safety factor: 4:1

Hydraulic Hoses - Standard Hoses - H SOU

Technical data

| Код товара | Код | Size | Model | Max. working pressure bar/Mpa | connection A | connection B |
|---------------|---------|------|---------|----------------------------------|---------------|---------------|
| 5611100572101 | H 1 SOU | 1 m | H 1 SOU | 720 / 72 | 3/8" NPT male | coupler A 119 |
| 5611100572102 | H 2 SOU | 2 m | H 2 SOU | 720 / 72 | 3/8" NPT male | coupler A 119 |
| 5611100572103 | H 3 SOU | 3 m | H 3 SOU | 720 / 72 | 3/8" NPT male | coupler A 119 |
| 5611100572105 | H 5 SOU | 5 m | H 5 SOU | 720 / 72 | 3/8" NPT male | coupler A 119 |