


Web Lashing POWERTEX Trucker r-PET

Product information



The POWERTEX Trucker r-PET lashing is a 2-part lashing and used for professional haulers.

The lashing is made from **recycled** high-strength polyester (r-PET) yarn, Cr6 free steel ratchets and hooks. Because the webbing is made from r-PET yarn, this product has a **42% CO₂ reduction*** compared to the standard Trucker Lashing.

This lashing is part of Lifting Solution Group's [Aspire range™](#). In November 2023, this product won the prestigious LEEA Sustainable Award.

Sustainability Fact Sheet Available (see tab documents drop-down menu)

Suitable for professional transporters looking for extra high strength and durability in a web lashing.

- Strong and durable with LC 2500 daN and STF 350 daN
- Webbing has min. breaking strength of 7500 daN
- Blue webbing with 2500 daN print for easy identification
- Both the long part and short part carry blue identification labels
- Label gives information on STF and lashing capacity for different lashing connections
- Each part is marked with a unique serial number for safe equipment registration
- The blue information label is protected by an layer of transparent plastic for long life
- Year/Month calendar printed on the label where latest inspection date can be marked or punched
- All lashings carry a white label with important warning instructions and user instruction pictogram, and information about the Aspire Range™
- Each lashing is marked with QR code to access the full user manual
- Cr6 free galvanization – better for health and environment
- Trucker can be supplied with other lengths and other end fittings on request.

Safety factor: Webbing min. 3, rachets min. 2 and hooks min. 2

*A 3rd party climate LCA with a cradle-to-gate perspective according to ISO14067 has shown that our r-PET web lashings have 42% fewer CO₂ emissions than our standard product. This means that our products are not only better for the environment but also make a positive

contribution to reducing CO2 emissions.

Marking: According to standard

Standard: EN 12195-2

Код товара	LC daN	2xLC (daN)	Длина м m	Band width mm	Design	Fitting	Цвет	Вес kg
701401002200250	2 500	5 000	10	50	2-part	Wire hook double	Синий	2,75