



Rope Pear Socket type S

Product information

The pear socket type S is specially designed for endfitting of a steel wire rope, and the breaking load is related to steel wire ropes with a smaller diameter that have a higher breaking load. Such as 8 strand and/or compacted wire ropes.

Safety factor: 5:1

Код товара	Код	Rope Ø range mm	WLL ton	MBL	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	Вес kg
122102400110	RPS-924	22-24	11	70	192	133	40	325	31	27	40	58	29	3,8
122102700110	RPS-1026	25-27	13	85	212	143	43	375	35	30,5	43	60	32	4,8
122103000110	RPS-1130	28-30	15	95	239	156	45	400	36	31,5	50	70	35	5,9
122103300110	RPS-1232	31-33	17	110	249	165	52	425	39	34,5	57	72	38	7
122103600110	RPS-1336	34-36	21	125	257	184	55	450	43	36,5	60	80	42	9,3
122104000110	RPS-1440	37-40	26	155	297	192	60	475	47	40	62	80	46	11,6
122104800110	RPS-1548	46-48	30	180	329	192	74	575	51	44	66	80	57	12,4
122104400110	RPS-3221	42-44	32,5	189	314	204	66	425	53	46	70	80	49	13,8
122104800111	RPS-1648	46-48	36	215	343	218	70	500	56	50	75	90	54	15

Blueprint

