



## Aluminum Lever Hoist Powertex PALH-S1

### Product information

#### **POWERTEX**

Extremely small and lightweight aluminum lever hoist. It weighs only approximately 50% of a similar standard lever hoist. The hoist can be used for lifting as well as pulling. 250 kg-750 kg hoists are delivered with a handy carrying/belt bag.

#### Features:

- Safe - Each hoist is dynamic proof load tested 1,5 x WLL before leaving the factory
- Compact, lightweight construction with aluminum covers
- Durable construction with powder coated finish and plated frame parts
- Lever hoist is chromium 6 free
- Sealed bearings inside maximize efficiency and serviceability.
- Sprocket wheel surface treated against wear and corrosion
- Safe and well covered automatic load reaction break
- Equipped with double brake pawls
- Fine calibrated Electro Galvanized (European made) load chain for smooth operation
- Swivel hooks at both ends makes in line positioning easy
- Hooks are designed to open at overload instead of breaking
- Hooks fitted with heavy duty steel safety latches
- Hook have Deformation Check Dots forged into side for overload detection
- RFID equipped (chip) for easy service and inspection
- QR code for on-site access to Multilanguage user manuals
- Test certificate and Declaration of Conformity enclosed with each hoist
- 14 language User manual enclosed with each hoist
- Spare parts available

**Marking:** According to standard, CE-marked

**Standard:** EN 13157, EN 818-7

**Safety factor:** 4:1

Код товара	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand force max. kg	a mm	b mm	c mm	d mm	e mm	f mm	g mm	s mm	t mm	Bec kg
500500030150460	0,25	1,5	1	PALH-S1/250KG	3 x 9	29	87	68	200	145	55,5	35,5	21	32	11	1,45
500500030300460	0,25	3	1	PALH-S1/250KG	3 x 9	29	87	68	200	145	55,5	35,5	21	32	11	1,95
500500050150460	0,5	1,5	1	PALH-S1/500KG	4 x 12	27	100,5	81	250	160	62,5	42	24,5	34,5	12	2,5
500500050300460	0,5	3	1	PALH-S1/500KG	4 x 12	27	100,5	81	250	160	62,5	42	24,5	34,5	12	3,3
500500080150460	0,75	1,5	1	PALH-S1/750KG	5 x 15	33	105	92	260	180	64	42	28,5	35,5	14	3,4
500500080300460	0,75	3	1	PALH-S1/750KG	5 x 15	33	105	92	260	180	64	42	28,5	35,5	14	4,3
500500150150460	1,5	1,5	1	PALH-S1/1500KG	7,1 x 20,1	42	122	109	330	220	68,5	52	35	42,5	21,5	6,27
500500150300460	1,5	3	1	PALH-S1/1500KG	7,1 x 20,1	42	122	109	330	220	68,5	52	35	42,5	21,5	8,2
500500300150460	3	1,5	2	PALH-S1/3000KG	7,1 x 20,1	43	122	160	432	220	68,5	61,9	43	50	24,5	9,11
500500300300460	3	3	2	PALH-S1/3000KG	7,1 x 20,1	43	122	160	432	220	68,5	61,9	43	50	24,5	12,4

# Blueprint

