

Welded Master Link X-002

Product information



Welded Master Link designed for 1-2 legs Wire Rope and Chain Slings. The engineered flat makes it simple to insert wire rope thimbles on our links. Suitable for omega links.

At least 25% greater WLL than traditional Grade 8 products.

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Tempering temperature at a minimum of 400°C.

[... Read more](#)

Marking: According to standard, CE-marked


Standard: EN 1677-4

Safety factor: 4:1

Класс: 10

Welded Master Link X-002

Blueprint



Technical data

Код товара	Код	WLL ton	EWL mm	For chain, 1-leg mm	For chain, 2-leg mm	A mm	B mm	D mm	Bec kg
402100280420	BD-13	2,8	110	7,8	6	110	60	13	0,3
402100400420	BD-16	4	110	10	7,8	110	60	16	0,5
402100670420	BD-19	6,7	135	13	10	135	75	19	0,9
402100850420	BD-22	8,5	160	13	10	160	90	22	1,5
402101150420	BD-28	11,5	180	16	13	180	100	28	2,7
402101700420	BD-32	17	200	20	16	200	110	32	3,9
402102510420	BD-36	25,1	260	22	20	260	140	36	6,3
402103830420	BD-45	38,3	300	26	22	300	180	45	11,8
402104500420	BD-50	45	300	32	26	300	200	50	15,2