Lifting Solutions Group
Axel Johnson International

# Master Link Assembly X-006

## Product information



- Welded Master Link designed for 3-4 legs Chain, Wire Rope and Webbing Slings.
- The engineered flat makes it simple to insert wire rope thimbles on our links. Suitable for omega links.
- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Manufactured in accordance with EN 1677- 4 and ASME B30.26.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL
... *Read more*

**Marking:** According to standard, CE-mark
**Standard:** EN 1677-4

**Safety factor:** 4:1
**Класс:** 10


**Certex Polska**
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Master Link Assembly X-006

## Blueprint




## Technical data

| Код товара | Код | Chain diameter mm | WLL ton | EWL mm | Proof Load kN | Can be used up to single hook acc. to DIN 15401 no. | D mm | A mm | B mm | d mm | a mm | b mm | Вес kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 402100420410 | BD-19 + 2 DD+13 | 6 | 4,2 | 189 | 103 | 5 | 19 | 135 | 75 | 13 | 54 | 25 | 1,3 |
| 402100820410 | BD-22 + 2 DD+16 | 7-8 | 8,2 | 230 | 201 | 6 | 22 | 160 | 90 | 16 | 70 | 34 | 2,2 |
| 402101070410 | BD-28 + 2 DD+19 | 10 | 10,7 | 265 | 262 | 8 | 28 | 180 | 100 | 19 | 85 | 40 | 3,9 |
| 402101570410 | BD-32 + 2 DD+22 | 13 | 15,7 | 315 | 385 | 10 | 32 | 200 | 110 | 22 | 115 | 50 | 6,1 |
| 402102220410 | BD-36 + 2 DD+28 | 16 | 22,2 | 325 | 544 | 16 | 36 | 260 | 140 | 28 | 140 | 65 | 10,6 |
| 402103410410 | BD-50 + 2 DD+32 | 20 | 34,1 | 450 | 835 | 32 | 50 | 300 | 200 | 32 | 150 | 70 | 21,2 |
| 402104000410 | BD-50 + 2 DD+36 | 22 | 40 | 470 | 980 | 32 | 50 | 300 | 200 | 36 | 170 | 75 | 23,8 |

**Certex Polska**
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved