

Master Link Assembly X-006

Product information



- Welded Master Link designed for 3-4 legs Chain, Wire Rope and Webbing Slings.
- The engineered flat makes it simple to insert wire rope thimbles on our links. Suitable for omega links.
- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Manufactured in accordance with EN 1677- 4 and ASME B30.26.


When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL
... [Read more](#)

Marking: According to standard, CE-marked
Standard: EN 1677-4

Safety factor: 4:1
Класс: 10

Master Link Assembly X-006

Blueprint



Technical data

Код товара	Код	Chain diameter mm	WLL ton	EWL mm	Proof Load kN	Can be used up to single hook acc. to DIN 15401 no.	D mm	A mm	B mm	d mm	a mm	b mm	Вес kg
402100420410	BD-19 + 2 DD+13	6	4,2	189	103	5	19	135	75	13	54	25	1,3
402100820410	BD-22 + 2 DD+16	7-8	8,2	230	201	6	22	160	90	16	70	34	2,2
402101070410	BD-28 + 2 DD+19	10	10,7	265	262	8	28	180	100	19	85	40	3,9
402101570410	BD-32 + 2 DD+22	13	15,7	315	385	10	32	200	110	22	115	50	6,1
402102220410	BD-36 + 2 DD+28	16	22,2	325	544	16	36	260	140	28	140	65	10,6
402103410410	BD-50 + 2 DD+32	20	34,1	450	835	32	50	300	200	32	150	70	21,2
402104000410	BD-50 + 2 DD+36	22	40	470	980	32	50	300	200	36	170	75	23,8