

Enlarged Welded Master Link Assembly X-007

Product information



Welded Master Link designed for 3-4 legs Wire Rope and Chain Slings.

At least 25% greater WLL than traditional Grade 8 products.

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.

... [Read more](#)

Marking: According to standard, CE-marked


Standard: EN 1677-4

Safety factor: 5:1

Класс: 10

Enlarged Welded Master Link Assembly X-007

Blueprint



Technical data

Код товара	Chain diameter mm	WLL ton	Proof Load kN	Can be used up to single hook acc. to DIN 15401 no.	D mm	A mm	B mm	d mm	a mm	b mm	Bec kg
402100530530	7-8	5,3	130	6	19	160	90	16	140	70	2,4
402100890530	10	8,9	218	16	25	275	145	19	160	90	5,2
402101290530	10	12,9	316	16	28	275	145	22	180	100	7,1
402101700530	13	17	417	16	32	275	145	25	210	115	10
402102360530	16	23,6	578	16	36	275	145	28	190	100	12,2
402102810530	16	28,1	688	20	40	300	160	32	275	145	19,2
402103830530	20	38,3	938	25	45	340	180	36	285	155	26,5