

Clevis Self Locking Hook X-026

Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Manufactured in accordance with EN 1677-3 and ASME B30.26.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C.
- Magnaflux crack detection is performed 100% on each batch.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL
... [Read more](#)

Marking: According to standard


Standard: EN 1677-3

Safety factor: 4:1

Класс: 10

Clevis Self Locking Hook X-026

Blueprint



Technical data

Код товара	Chain diameter mm	WLL ton	EWL mm	A mm	H mm	K mm	P mm	T mm	Bec kg
402300140730	6	1,4	93	7	19	94	28	15	0,4
402300250730	7-8	2,5	119	9	24	119	34	20	0,9
402300400730	10	4	142	11	30	142	44	26	1,4
402300670730	13	6,7	178	15	39	178	52	30	3
402301000730	16	10	213	18	49	213	60	36	5
402301600730	20	16	244	25	65	251	70	53	11
402301900730	22	19	273	24	63	273	80	49	13,5