


## Steel Wire Rope Ropetex S19 Stainless Steel

### Product information



Stay rope



Agriculture and livestock



### ROPETEX



ROPETEX S19 is a stainless steel wire rope. It's very corrosion resistant and durable, well suited for marine applications. The S19 rope has very little stretch which makes it excellent for standing rigging, stays, controls and architectural balustrades and green walls.

ROPETEX S19 can be provided with swaged terminals as end fittings.

[... Read more](#)

**Marking:** According to standard

**Standard:** EN 12385-10

*except material*

**Fill factor:** 0,74

## Steel Wire Rope Ropetex S19 Stainless Steel

### Technical data

Код товара	Rope diameter mm	Tensile strength N/mm <sup>2</sup>	Finish	Rope lay	Min. breaking force kN	Steel area mm <sup>2</sup>	Lubrication	Bec kg/100m
108100101620018	1	1 570	Stainless	S	0,83	0,58	No-Lube	0,49
108100102620018	1	1 570	Stainless	Z	0,83	0,58	No-Lube	0,49
108100131620018	1,25	1 570	Stainless	S	1,29	0,91	No-Lube	0,74
108100132620018	1,25	1 570	Stainless	Z	1,29	0,91	No-Lube	0,74
108100151620018	1,5	1 570	Stainless	S	1,86	1,31	No-Lube	1,09
108100152620018	1,5	1 570	Stainless	Z	1,86	1,31	No-Lube	1,09
108100201620018	2	1 570	Stainless	S	3,3	2,33	No-Lube	1,94
108100202620018	2	1 570	Stainless	Z	3,3	2,33	No-Lube	1,94
108100251620018	2,5	1 570	Stainless	S	5,16	3,65	No-Lube	3,03
108100252620018	2,5	1 570	Stainless	Z	5,16	3,65	No-Lube	3,03
108100301620018	3	1 570	Stainless	S	7,43	5,25	No-Lube	4,37
108100302620018	3	1 570	Stainless	Z	7,43	5,25	No-Lube	4,37
108100401620018	4	1 570	Stainless	S	13,2	9,34	No-Lube	7,76
108100402620018	4	1 570	Stainless	Z	13,2	9,34	No-Lube	7,76
108100501620018	5	1 570	Stainless	S	20,6	14,6	No-Lube	12,1
108100502620018	5	1 570	Stainless	Z	20,6	14,6	No-Lube	12,1
108100601620018	6	1 570	Stainless	S	29,7	21	No-Lube	17,5
108100602620018	6	1 570	Stainless	Z	29,7	21	No-Lube	17,5
108100701620018	7	1 570	Stainless	S	40,5	28,6	No-Lube	23,8
108100702620018	7	1 570	Stainless	Z	40,5	28,6	No-Lube	23,8
108100801620018	8	1 570	Stainless	S	52,8	37,4	No-Lube	31
108101001620018	10	1 570	Stainless	S	82,6	58,4	No-Lube	48,5