



Universal Swivel VIP RUD UW-PP

Product information

- With a ball bearing which enables swiveling under load.
- Patented clevis system facilitating a universal connection
- Can be loaded in all directions with the shortest combination possibilities.

Assemble only with approved RUD - VIP - chain and ring components:

- VIP-Cobra eye hook VCÖH
- Oval-Link PP-B for PowerPoint

The VIP-Chain connection is fool-proof. When assembling, especially with the ring components, pay attention to the correct WLL! Not suitable for permanent use and swiveling under full load. Connecting bolt and tensioning sleeve are pre-assembled. The DGUV-rule 109-017 stipulates that slings never be used while in a twisted condition. This requirement is automatically met by the UW-PP because of the integrated ball bearing.

Safety factor: 4:1

Класс: 10

Код товара	Код	WLL ton	A mm	B mm	C mm	T mm	Вес kg
422500060560	UW-PP-4	0,63	32	4,8	13	56	0,2
422500150560	UW-PP-6	1,5	38	7	16	68	0,42
422500250560	UW-PP-8	2,5	52	9,1	20	88	1
422500400560	UW-PP-10	4	66	11	26	106	1,91
422500670560	UW-PP-13	6,7	80	14,5	30	131	3,64
422501000560	UW-PP-16	10	86	17,6	37	141	4,87
422503150560	VUW-28	31,5	148	-	-	183	27,3

Blueprint

