

## Weld-on Lifting Ring RUD VRBS-FIX

---

### Product information



Load ring for plane surfaces. 180° pivoting. Continuous weld seam reduces likelihood of subsurface corrosion.

- No complex leveling of the components to each other
- No crevice corrosion: endless HY weld seam
- Clamping spring holds all parts together

... [Read more](#)


---

**Marking:** According to standard, CE-marked  
**Standard:** EN 1677-1

**Safety factor:** 4:1

## Weld-on Lifting Ring RUD VRBS-FIX

### Blueprint



### Technical data

Код товара	Код	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	T mm	Вес kg
42157999019	VRBS-FIX - 4t	4	60	14	39	48	132	69	74	0,94
42157999020	VRBS-FIX - 6.7t	6,7	88	20	50	60	167	91	97	2,24
42157999021	VRBS-FIX - 10t	10	100	22	60	65	191	100	108	3,72
42157999301	VRBS-FIX - 16t	16	130	30	72	90	267	134	140	8,23
42157999302	VRBS-FIX - 31.5t	31,5	160	42	99	130	366	195	202	18,36
42157906272	VRBS-FIX - 50t	50	246	70	148	230	596	335	330	64,7
42157906273	VRBS-FIX - 100t	100	320	97	195	250	763	392	390	148,2