



## Master Link 4-legs RUD VIP

### Product information

VAK 4-leg master link with 4 all direction movable, welded VRG connectors. Thus ensuring that only the correct chain diameter and number of legs can be connected. VIP-Master link is marked by the RUD-ID-TAG® (RFID chip) and with the clear identification number distinguished. Complete identification tag with an integrated testing gauge. Pre-assembled connecting bolt and tensioning sleeve.

**Marking:** According to standard

**Standard:** EN 1677-4

**Safety factor:** 4:1

**Knacc:** 10

| Код товара  | Код                         | WLL ton | A mm | B mm | C mm | D, mm | E mm | F mm | T mm | Вес kg |
|-------------|-----------------------------|---------|------|------|------|-------|------|------|------|--------|
| 42157984447 | VAK-3/4-4                   | 1,32    | 10   | 35   | 60   | -     | -    | -    | 106  | 0,34   |
| 42157100742 | VAK-4-6                     | 3,15    | 18   | 75   | 135  | -     | -    | -    | 217  | 1,8    |
| 42157100748 | VSAK-4-6 / 140              | 3,15    | 22   | 140  | 260  | -     | -    | -    | 342  | 3,19   |
| 42157100751 | VSAK-4-6 / 190              | 3,15    | 22   | 190  | 350  | -     | -    | -    | 432  | 3,83   |
| 42157100743 | VAK-4-8                     | 5,25    | 22   | 90   | 160  | -     | -    | -    | 268  | 3,4    |
| 42157100749 | VSAK-4-8 / 140              | 5,25    | 26   | 140  | 260  | -     | -    | -    | 367  | 4,86   |
| 42157100752 | VSAK-4-8 / 190              | 5,25    | 26   | 190  | 350  | -     | -    | -    | 457  | 5,9    |
| 42157100744 | VAK-4-10                    | 8,4     | 26   | 100  | 180  | -     | -    | -    | 311  | 5,5    |
| 42157100750 | VSAK-4-10 / 140             | 8,4     | 32   | 140  | 260  | -     | -    | -    | 391  | 7,99   |
| 42157100753 | VSAK-4-10 / 190             | 8,4     | 32   | 190  | 350  | -     | -    | -    | 481  | 9,34   |
| 42157100755 | VSAK-4-10 / 250             | 8,4     | 36   | 250  | 460  | -     | -    | -    | 591  | 13,47  |
| 42157100745 | VAK-4-13                    | 14,1    | 32   | 110  | 200  | -     | -    | -    | 373  | 10,4   |
| 42157100754 | VSAK-4-13 / 190             | 14,1    | 36   | 190  | 350  | -     | -    | -    | 523  | 14     |
| 42157100756 | VSAK-4-13 / 250             | 14,1    | 40   | 250  | 460  | -     | -    | -    | 634  | 18,95  |
| 42157100746 | VAK-4-16                    | 21,2    | 36   | 140  | 260  | -     | -    | -    | 470  | 17,6   |
| 42157100757 | VSAK-4-16 / 250             | 21,2    | 51   | 250  | 460  | -     | -    | -    | 671  | 32,42  |
| 42157104181 | VAK-4-20                    | 33,6    | 51   | 190  | 350  | -     | -    | -    | 614  | 39,1   |
| 42157993210 | VSAK-4-20 / 250 with VVS-20 | 33,6    | 54   | 250  | 460  | 36    | 75   | 170  | 754  | 48,36  |
| 42157100747 | VAK-4-22                    | 42      | 51   | 190  | 350  | -     | -    | -    | 644  | 45,7   |
| 42157993211 | VSAK-4-22 / 250 with VVS-22 | 42      | 57   | 250  | 460  | 40    | 80   | 170  | 763  | 56,7   |

## Blueprint

