

Master Link 4-legs RUD VIP

Product information



VAK 4-leg master link with 4 all direction movable, welded VRG connectors. Thus ensuring that only the correct chain diameter and number of legs can be connected. VIP-Master link is marked by the RUD-ID-TAG® (RFID chip) and with the clear identification number distinguished. Complete identification tag with an integrated testing gauge. Pre-assembled connecting bolt and tensioning sleeve.

[... Read more](#)

Marking: According to standard


Standard: EN 1677-4

Safety factor: 4:1

Класс: 10

Master Link 4-legs RUD VIP

Blueprint



Technical data

Код товара	Код	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	T mm	Вес kg
42157984447	VAK-3/4-4	1,32	10	35	60	-	-	-	106	0,34
42157100742	VAK-4-6	3,15	18	75	135	-	-	-	217	1,8
42157100748	VSAK-4-6 / 140	3,15	22	140	260	-	-	-	342	3,19
42157100751	VSAK-4-6 / 190	3,15	22	190	350	-	-	-	432	3,83
42157100743	VAK-4-8	5,25	22	90	160	-	-	-	268	3,4
42157100749	VSAK-4-8 / 140	5,25	26	140	260	-	-	-	367	4,86
42157100752	VSAK-4-8 / 190	5,25	26	190	350	-	-	-	457	5,9
42157100744	VAK-4-10	8,4	26	100	180	-	-	-	311	5,5
42157100750	VSAK-4-10 / 140	8,4	32	140	260	-	-	-	391	7,99
42157100753	VSAK-4-10 / 190	8,4	32	190	350	-	-	-	481	9,34
42157100755	VSAK-4-10 / 250	8,4	36	250	460	-	-	-	591	13,47
42157100745	VAK-4-13	14,1	32	110	200	-	-	-	373	10,4
42157100754	VSAK-4-13 / 190	14,1	36	190	350	-	-	-	523	14
42157100756	VSAK-4-13 / 250	14,1	40	250	460	-	-	-	634	18,95
42157100746	VAK-4-16	21,2	36	140	260	-	-	-	470	17,6
42157100757	VSAK-4-16 / 250	21,2	51	250	460	-	-	-	671	32,42
42157104181	VAK-4-20	33,6	51	190	350	-	-	-	614	39,1
42157993210	VSAK-4-20 / 250 with VVS-20	33,6	54	250	460	36	75	170	754	48,36
42157100747	VAK-4-22	42	51	190	350	-	-	-	644	45,7
42157993211	VSAK-4-22 / 250 with VVS-22	42	57	250	460	40	80	170	763	56,7