Lifting Solutions Group
Axel Johnson International

Wall Panel Lifting Gear

Product information



The galvanized wall panel lifting gear is used for the laying of horizontally positioned AAC wall panels. The profiled clamps ensure a high grip. If the safety chain is applied a transport high above the ground is permitted. The safety chain can be released by a tension rope of 10 m length.

Features:

- Used for the laying of horizontally positioned AAC wall panels
- Profiled clamps ensure a high grip
- If the safety chain is applied a transport high above the ground is permitted
- The safety chain can be released by a tension rope of 10 m length
- Carrying capacities 675 kg, 1,000 kg and 1,400 kg available

... *Read more*

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Wall Panel Lifting Gear

Blueprint



Technical data

Код товара	Код	WLL ton	Jaw width mm	L mm	B mm	H mm	Вес kg
502100072303070	PIZa 1	0,675	70-230	520	70-230	285	43
502100103103070	PIZa 2	1	150-310	660	150-310	330	50
502100143103070	PIZa 4	1,4	150-310	1 000	150-310	330	65

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved