



Short Link Lifting Chain POWERTEX PSL Grade 8

Product information

High-quality calibrated lifting chain intended for use in demanding applications like Grade 8 chain slings and chain lashings.

Features:

- Safe - each chain link is proof load tested 2,5 x WLL in the factory prior delivery
- Safe - each production batch is tested to meet the min. breaking force
- Ductile - Min. 20% elongation shall be achieved before failure
- Accurate - each length of chain is calibrated in the factory prior delivery
- Consistent – PSL chains are made in automatic chain welding machines
- Compliant - the chains fulfill EN 818-2 and the Machinery directive 2006/42/EC
- Each barrel includes a 14 language 2.2 Certificate and EC/UKCA Declaration of Conformity
- Each chain length carries a chain tag at the end for quick and positive identification
- The barrel is marked with an info sticker that allow quick and positive identification of the chain inside

Marking: According to standard, CE-marked, UKCA-marked

Standard: EN 818-2, AS 2321

Safety factor: 4:1

Класс: 8

Код товара	Chain diameter mm	WLL ton	Min. breaking force kN	Proof Load kN	d mm	p mm	W1	W2	Bec kg/m
203100600000200	6	1,12	45,2	28,3	6	18	7,8	22,2	0,8
203100800000200	8	2	80,4	50,3	8	24	10,4	29,6	1,5
203101000000200	10	3,15	126	78,5	10	30	13	37	2,3
203101300000200	13	5,3	212	133	13	39	16,9	48,1	3,9
203101600000200	16	8	322	201	16	48	20,8	59,2	5,8
203102000000200	20	12,5	503	314	20	60	26	74	8,9

Blueprint

