

Fast Connector Socket FCS - with bolt

Product information




Forged clevis fittings with bolt, nut and cutterpin for fast connection of steel wire rope. Connector shall be used with non-rotating or cat 1. rotation resistant wire rope only.

The connector has to be moulded/casted on the steel wire rope with *wirelock resin*
... [Read more](#)

Fast Connector Socket FCS - with bolt

Blueprint



Technical data

Код товара	Код	Rope Ø range mm	MBL ton	Finish	A mm	B mm	C mm	Ø H mm	Ø P mm	T mm	W mm	D mm	Ø D mm	Ø J mm	K mm	TB mm	TL mm	Вес kg
122101300155	FCS 701 B	11-13	20	Painted	62	61	27	15	25	12	25	50	33	49	46	80	150	1,6
122101300152	FCS 701 B.G	11-13	20	Galvanized	62	61	27	15	25	12	25	50	33	49	46	80	150	1,6
122101600155	FCS 702 B	13-16	25	Painted	72	78	32	18	30	14	32	58	38	60	59	96	182	2,6
122101600152	FCS 702 B.G	13-16	25	Galvanized	72	78	32	18	30	14	32	58	38	60	59	96	182	2,6
122101900155	FCS 703 B	16-19	40	Painted	85	93	40	21	35	16	38	70	45	70	69	107	218	4,5
122101900152	FCS 703 B.G	16-19	40	Galvanized	85	93	40	21	35	16	38	70	45	70	69	107	218	4,5
122102200155	FCS 704 B	20-22	55	Painted	102	106	45	24	41	19	44	80	50	82	81	123	253	6,5
122102200152	FCS 704 B.G	20-22	55	Galvanized	102	106	45	24	41	19	44	80	50	82	81	123	253	6,5
122102600155	FCS 705 B	23-26	75	Painted	115	123	60	28	51	22	51	104	60	95	90	141	298	11
122102600152	FCS 705 B.G	23-26	75	Galvanized	115	123	60	28	51	22	51	104	60	95	90	141	298	11
122102900155	FCS 706 B	27-29	90	Painted	140	152	65	32	57	25	57	114	70	107	116	160	357	16
122102900152	FCS 706 B.G	27-29	90	Galvanized	140	152	65	32	57	25	57	114	70	107	116	160	357	16