



## Single Sheave Crane Blocks

### Product information

**General:**

- Standard fitted with becket, cylindrical roller bearing and reeving guide.
- Standard fitted with Crosby type of swivel only hook (319AN style), including safety latch and split pin.
- Standard painted yellow (no striping).
- This crane block may be used with 2 lines only as well.
- Sheaves may be adjustud for other wire rope diameters.
- Becket suitable for connecting Open Wedge Socket for indicated wire rope.
- Becket can not be adjusted.

Код товара	WLL ton	Sheave dia. mm	Wire Ø mm	øD1	øD2	B mm	O mm	S mm	TA mm	TB mm	TL mm	T mm	øZ	Bec kg
6097HB2101115E	5	250/210	11	250	210	348	34	30	320	103	523	20	27	41
6097HB2201315E	5	260/221	13	260	221	353	34	30	353	109	525	22	27	67
6097HB2201418E	8	260/218	14	260	218	390	43	35	330	121	571	28	32	80
6097HB2551318E	8	300/255	13	300	255	426	43	30	370	101	621	22	27	89
6097HB2551618E	8	300/252	16	300	252	420	43	35	370	111	621	28	32	94
6097HB25516110E	10	300/252	16	300	252	459	52	35	370	127	659	28	32	91
6097HB22014110E	10	260/218	14	260	218	429	52	35	330	137	609	28	32	93
6097HB30516110E	10	350/305	16	350	305	499	52	35	435	107	739	28	33	113
6097HB34518112E	12	400/345	18	400	345	557	57	45	500	125	832	35	37	162
6097HB39020116E	16	450/390	20	450	390	592	57	50	550	131	917	35	43	206
6097HB43022120E	20	500/430	22	500	430	592	76	50	600	148	1 032	40	43	284

Blueprint

