

## Lifting chain, grade 80

---

### Product information

Short link lifting chain grade 80 is manufactured according to EN 818-2 standard.

... [Read more](#)



---

**Marking:** According to standard  
**Standard:** EN 818-2

**Safety factor:** 4:1  
**Класс:** 8

## Lifting chain, grade 80

### Blueprint



### Technical data

| Код товара      | Chain diameter mm | WLL ton | A mm | B mm | D mm | Бес kg/m |
|-----------------|-------------------|---------|------|------|------|----------|
| 203100600000100 | 6                 | 1,12    | 18   | 9    | 6    | 0,8      |
| 203100800000100 | 8                 | 2       | 24   | 12   | 8    | 1,35     |
| 203101000000100 | 10                | 3,15    | 30   | 14   | 10   | 2,15     |
| 203101300000100 | 13                | 5,3     | 39   | 19   | 13   | 3,5      |
| 203101600000100 | 16                | 8       | 48   | 23   | 16   | 5,5      |
| 203102000000100 | 20                | 12,5    | 60   | 25   | 20   | 8,4      |
| 203102200000100 | 22                | 15      | 66   | 28   | 22   | 10,35    |
| 203102600000100 | 26                | 21,2    | 78   | 35   | 26   | 15,8     |
| 203103200000100 | 32                | 31,5    | 96   | 43   | 32   | 23       |