

Swivel Bearing Hoist Hook X-175N

Product information



- 20,000 cycle fatigue rated to 1.5 times of 4:1 WLL
- All swivel hoist hooks are 100% magnaflux crack detected.
- Ball bearing performs fully swivel under load.

... [Read more](#)


Marking: CE-marked

Safety factor: 4:1

Класс: 10

Swivel Bearing Hoist Hook X-175N

Blueprint



Technical data

| Код товара | Код | Chain diameter mm | WLL ton | A mm | B mm | C mm | D mm | G mm | H mm | K mm | L mm | P mm | P1 mm | T mm | Вес kg |
|--------------|-----|-------------------|---------|------|------|------|------|------|------|------|------|------|-------|------|--------|
| 420500250920 | CC | 7-8 | 2,5 | 36 | 29 | 26 | 13 | 90 | 27 | 145 | 184 | 24 | 20 | 22 | 1 |
| 420500400920 | DD | 10 | 4 | 41 | 35 | 29 | 16 | 102 | 29 | 172 | 217 | 28 | 25 | 24 | 1,6 |
| 420500670920 | EE | 13 | 6,7 | 46 | 44 | 38 | 21 | 122 | 38 | 218 | 277 | 35 | 31 | 31 | 3,3 |
| 420501000920 | FF | 16 | 10 | 61 | 50 | 49 | 23 | 160 | 48 | 261 | 332 | 43 | 39 | 35 | 5,6 |
| 420501600920 | GG | 18-20 | 16 | 74 | 82 | 62 | 25 | 196 | 56 | 327 | 410 | 61 | 57 | 47 | 9,5 |
| 420501900920 | HH | 22 | 19 | 97 | 96 | 65 | 33 | 221 | 64 | 372 | 471 | 72 | 62 | 56 | 16 |
| 420502650920 | JJ | 26 | 26,5 | 123 | 116 | 71 | 51 | 277 | 76 | 469 | 599 | 86 | 81 | 68 | 33,5 |
| 420504000920 | KK | 32 | 40 | 123 | 116 | 87 | 51 | 353 | 93 | 503 | 651 | 89 | 83 | 76 | 45 |