Lifting Solutions Group
Axel Johnson International

Clevis Sling Hook X-043/S Grade 10

Product information



At least 25% greater WLL than traditional Grade 8 products.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Tempering temperature minimum 400°C.
Magnaflux crack detection is performed 100% on each batch.

... *Read more*

Marking: According to standard
Standard: EN 1677-2

Safety factor: 4:1
Класс: 10


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Clevis Sling Hook X-043/S Grade 10

Blueprint



Technical data

Код товара	Chain diameter mm	WLL ton	EWL mm	A mm	H mm	K mm	P1 mm	T mm	Вес kg
402300140700	6	1,4	79	7	18	79	23	15	0,3
402300250700	7-8	2,5	98	9	22	98	27	18	0,6
402300400700	10	4	122	12	30	122	34	24	1,1
402300670700	13	6,7	147	15	37	147	44	30	2,3
402301000700	16	10	166	17	41	166	48	39	3,8
402301600700	20	16	207	24	64	207	57	48	8,7
402301900700	22	19	217	25	61	217	73	52	9,5

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved