

Swivel Grip Safe Locking Hook X-952N



Product information

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL. Magnaflux crack detection is performed 100% on each batch. Built with ball bearing and enables full swivel feature under load.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Marking: According to standard

Standard: EN 1677-1

Safety factor: 4:1

Класс: 10

| Код товара | Chain diameter mm | WLL ton | EWL mm | A mm | B mm | D, mm | H, mm | K mm | Omm mm | Pmm mm | T mm mm | Wmm mm | Вес kg |
|--------------|-------------------|---------|--------|------|------|-------|-------|------|--------|--------|---------|--------|--------|
| 420500400960 | 10 | 4 | 225 | 41 | 35 | 16 | 31 | 226 | 49 | 71 | 27 | 137 | 2,4 |
| 420500670960 | 13 | 6,7 | 285 | 46 | 44 | 21 | 39 | 283 | 64 | 80 | 34 | 174 | 5,2 |
| 420501000960 | 16 | 10 | 345 | 61 | 50 | 23 | 47 | 347 | 78 | 114 | 39 | 212 | 8,4 |
| 420501600960 | 20 | 16 | 433 | 74 | 82 | 25 | 55 | 433 | 92 | 127 | 54 | 251 | 14,5 |
| 420501900960 | 22 | 19 | 475 | 97 | 96 | 33 | 59 | 476 | 98 | 151 | 56 | 258 | 20,4 |

Blueprint

