



## Eye Grab Hook X-041

### Product information

At least 25% greater WLL than traditional Grade 8 products.

Testing according to DIN PAS 1061 and ASTM A952/A 952M.

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.

Tempering temperature minimum 400°C.

Enables full WLL while in use, thanks to supporting wings which prevent chain link deformation.

**Marking:** According to standard

**Standard:** EN 1677-1

**Safety factor:** 4:1

**Класс:** 10

Код товара	Chain diameter mm	WLL ton	A mm	B mm	F mm	G, mm	K mm	Pmm mm	Bec kg
402300140740	6	1,4	13	7	26	8	50	8	0,2
402300250740	7-8	2,5	16	10	30	9	62	10	0,3
402300400740	10	4	20	13	40	13	82	13	0,6
402300670740	13	6,7	26	16	52	16	107	17	1,4
402301000740	16	10	30	18	70	20	132	21	2,4
402301600740	20	16	40	22	73	24	148	24	4
402301900740	22	19	42	24	86	26	166	26	5
402302650740	26	26,5	50	30	110	32	207	33	10,1
402304000740	32	40	62	37	130	42	266	42	24

## Blueprint

