Lifting Solutions Group
Axel Johnson International

Web Sling Connector X-016

Product information



At least 25% greater WLL than traditional Grade 8 products.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Tempering temperature minimum 400°C

... *Read more*

Marking: According to standard
Standard: EN 1677-1

Safety factor: 4:1
Класс: 10


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Web Sling Connector X-016

Blueprint



Technical data

Код товара	Chain diameter mm	WLL ton	EWL mm	A mm	B mm	D mm	K mm	W mm	Вес kg
402200140200	6	1,4	55	15	17	7	56	39	0,2
402200250200	7-8	2,5	62	18	23	9	63	39	0,3
402200400200	10	4	78	25	27	11	77	46	0,6
402200670200	13	6,7	95	30	37	16	97	53	1,1
402201000200	16	10	115	36	39	19	114	66	2
402201600200	20	16	132	42	46	22	132	79	3,2
402201900200	22	19	187	49	59	24	188	124	7,7

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved