Lifting Solutions Group
Axel Johnson International

Master Link Grab 1 Assy X-A06

Product information



At least 25% greater WLL than traditional Grade 8 products.
Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Fully integrated shortening hooks and master link.
No reduction in WLL when shortening chain.
Speedy assembly.
Light weight system.
Cost effective compared to slings which use multiple components.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

... *Read more*

Marking: According to standard, CE-mark
Standard: EN 1677-4

Safety factor: 4:1
Класс: 10


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Master Link Grab 1 Assy X-A06

Blueprint



Technical data

Код товара	Chain diameter mm	WLL ton	WLL 45- 60° ton	WLL 0°-45° т	D mm	A mm	B mm	K mm	Вес kg
402100290480	6	2,9	2,1	2,9	19	160	95	290	2,4
402100530480	8	5,3	3,8	5,3	22	170	105	342	4,6
402100840480	10	8,4	6,0	8,4	28	190	110	400	8,1
402101410480	13	14,1	10,1	14,1	32	230	130	503	15,8
402102100480	16	21	15,0	21,0	36	275	150	617	28,9

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved