Lifting Solutions Group
Axel Johnson International

# Shackles, SAE - bow model

## Product information



Shackles approved for lifting. Bow shackles are suitable for use when more than one attachment is to be made to the body (multi-leg systems), or to allow freedom of movement in the plane of the bow. Screw pin shackles are easily manipulated. They are typically suitable for non-permanent applications and one-off installations, when there is no tendency for the pin to unscrew and the shackle can be observed under operation.

... *Read more*

**Marking:** According to standard, CE-marked
**Standard:** US. FED. SPEC. RR-C-271F

**Safety factor:** 6:1


**Certex Polska**
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Shackles, SAE - bow model

## Blueprint




## Technical data

| Код товара | WLL ton | Size inch | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | I mm | M mm | N mm | Вес kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 4201SAK03PBP | 0,33 | 3/16 | 10 | 7 | 22 | 5 | 15 | 14 | 25 | 38 | 4 | 29 | 5 | 0,03 |
| 4201SAK05PBP | 0,5 | 1/4 | 12 | 8 | 29 | 7 | 20 | 16 | 33 | 47 | 5 | 35 | 5 | 0,05 |
| 4201SAK07PBP | 0,75 | 5/16 | 14 | 10 | 31 | 8 | 22 | 19 | 38 | 53 | 6 | 42 | 8 | 0,09 |
| 4201SAK10PBP | 1 | 3/8 | 17 | 11 | 37 | 10 | 26 | 23 | 45 | 63 | 7 | 52 | 10 | 0,14 |
| 4201SAK15PBP | 1,5 | 7/16 | 19 | 13 | 43 | 11 | 30 | 27 | 52 | 74 | 8 | 61 | 11 | 0,17 |
| 4201SAK20PBP | 2 | 1/2 | 21 | 16 | 48 | 13 | 34 | 30 | 59 | 84 | 10 | 69 | 13 | 0,33 |
| 4201SAK32PBP | 3,25 | 5/8 | 27 | 19 | 61 | 16 | 43 | 38 | 75 | 106 | 11 | 85 | 18 | 0,62 |
| 4201SAK47PBP | 4,75 | 3/4 | 32 | 23 | 72 | 19 | 51 | 46 | 89 | 126 | 13 | 101 | 21 | 1,07 |
| 4201SAK65PBP | 6,5 | 7/8 | 37 | 26 | 84 | 23 | 58 | 53 | 102 | 148 | 13 | 114 | 25 | 1,64 |
| 4201SAK85PBP | 8,5 | 1 | 43 | 29 | 96 | 26 | 69 | 61 | 119 | 167 | 14 | 129 | 27 | 2,28 |
| 4201SAK95PBP | 9,5 | 1-1/8 | 46 | 32 | 108 | 30 | 74 | 69 | 131 | 190 | 16 | 142 | 32 | 3,36 |
| 4201SAK120PBP | 12 | 1-1/4 | 52 | 35 | 119 | 33 | 93 | 76 | 146 | 210 | 18 | 156 | 35 | 4,31 |
| 4201SAK135PBP | 13,5 | 1-3/8 | 57 | 38 | 133 | 36 | 92 | 84 | 162 | 233 | 19 | 174 | 38 | 6,14 |
| 4201SAK170PBP | 17 | 1-1/2 | 61 | 42 | 146 | 39 | 99 | 92 | 175 | 254 | 21 | 187 | 41 | 7,8 |
| 4201SAK250PBP | 25 | 1-3/4 | 73 | 51 | 178 | 47 | 127 | 106 | 225 | 313 | 26 | 231 | 57 | 12,6 |
| 4201SAK350PBP | 35 | 2 | 83 | 57 | 197 | 53 | 146 | 122 | 253 | 348 | 31 | 263 | 61 | 20,4 |
| 4201SAK550PBP | 55 | 2-1/2 | 105 | 70 | 267 | 69 | 184 | 145 | 327 | 453 | 35 | 330 | 80 | 38,9 |
| 4201SAK850PBP | 85 | 3 | 127 | 82 | 330 | 76 | 200 | 165 | 367 | 546 | 38 | 490 | 105 | 70 |

**Certex Polska**
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved