

Turnable lifting point, grade 80

Product information



- turnable lifting point for all lifting directions.
- eye turns to the direction of the load
- bolts also available with 120 mm thread
- bolt grade 10.9


... [Read more](#)

Marking: According to standard, CE-marked
Standard: EN 1677-1

Safety factor: 4:1

Turnable lifting point, grade 80

Blueprint



Technical data

Код товара	WLL ton	Thread mm	Packing Qty.	Thread length mm	Tightening torque Nm	Thread pitch mm	A mm	B mm	C mm	D, mm	EL mm	F mm	G, mm	H, mm	S mm	SWmm mm	L1 mm mm	Bec kg
4215NS8P0803	0,3	M8	40	11	30	1,25	33	37	35	14	11	98	57	36	6	13	47	0,5
4215NS8P0803120	0,3	M8	-	120	30	1,25	33	37	35	14	120	98	57	36	6	13	156	0,5
4215NS8P10063	0,63	M10	40	16	60	1,5	33	37	36	14	16	98	57	36	6	17	52	0,5
4215NS8P10063120	0,63	M10	-	120	60	1,5	33	37	36	14	120	98	57	36	6	17	156	0,5
4215NS8P121	1	M12	40	18	100	1,75	33	37	44	14	18	98	57	36	8	19	54	0,5
4215NS8P121120	1	M12	-	120	100	1,75	33	37	44	14	120	98	57	36	8	19	156	0,5
4215NS8P1615	1,5	M16	40	24	150	2	33	37	46	14	24	98	57	36	10	24	60	0,5
4215NS8P1615120	1,5	M16	-	120	150	2	33	37	46	14	120	98	57	36	10	24	156	0,5
4215NS8P2025	2,5	M20	10	30	250	2,5	50	54	57	17	30	140	82	44	12	30	74	1,3
4215NS8P2025120	2,5	M20	-	120	250	2,5	50	54	57	17	120	140	82	44	12	30	164	1,3
4215NS8P244	4	M24	10	36	400	3	50	54	59	17	36	140	82	44	14	36	80	1,4
4215NS8P244120	4	M24	-	120	400	3	50	54	59	17	120	140	82	44	14	36	164	1,4
4215NS8P305	5	M30	6	48	500	3,5	60	65	81	23	48	170	99	62	17	46	110	3,1
4215NS8P305120	5	M30	-	120	500	3,5	60	65	81	23	120	170	99	62	17	46	182	3,1
4215NS8P368	8	M36	4	62	800	4	77	85	101	27	62	225	124	78	22	55	140	5,8
4215NS8P368120	8	M36	-	120	800	4	77	85	101	27	120	225	124	78	22	55	198	5,8
4215NS8P4215	15	M42	2	63	1 500	4,5	95	104	112	36	63	256	158	86	24	65	149	10,8
4215NS8P4215120	15	M42	-	120	1 500	4,5	95	104	112	36	120	256	158	86	24	65	206	10,8
4215NS8P4820	20	M48	2	72	2 000	5	95	104	120	36	72	259	158	90	27	75	162	11,6
4215NS8P4820120	20	M48	-	120	2 000	5	95	104	120	36	120	259	158	90	27	75	210	11,6