



Lifting eye Screw

Product information

Lifting for all lifting directions.

WLL for vertical lifting is marked on the eye.

The depth of the threaded hole has to be minimum:

d = diameter of the lifting eye thread

- 1*d for steel
- 1,25*d for cast iron
- 2*d for aluminum alloys
- 2,5*d for aluminum magnesium alloys

Marking: According to standard, CE-marked

Standard: EN 1677-1

Safety factor: 4:1

Код товара	WLL ton	Thread mm	Eye diameter mm	Thread pitch mm	D,	L	K,	M mm	ø mm	Вес kg
4215NS8R06	0,4	M6	16	1	28	42	13	M6	16	0,05
4215NS8R08	0,8	M8	20	1,25	39	51	15	M8	20	0,06
4215NS8R10	1	M10	25	1,5	45	63	18	M10	25	0,11
4215NS8R12	2	M12	30	1,75	54	75	22	M12	30	0,18
4215NS8R14	3	M14	35	2	63	88	28	M14	35	0,28
4215NS8R16	4	M16	35	2	63	88	28	M16	35	0,28
4215NS8R20	6	M20	40	2,5	72	101	30	M20	40	0,45
4215NS8R24	8	M24	50	3	90	128	38	M24	50	0,87
4215NS8R30	12	M30	60	3,5	108	154	45	M30	60	1,66
4215NS8R36	16	M36	70	4	126	183	55	M36	70	2,65
4215NS8R42	24	M42	80	4,5	144	212	65	M42	80	4,03
4215NS8R48	32	M48	90	5	166	238	70	M48	90	6,38

Blueprint

