



Cross spreader with 4-legged sling

Product information



General: The X-frames have a high point of oscillation which results in good balance. The table only shows a few examples of available sizes. Other lengths and working loads can be manufactured to suit a customers requirements. The frames can be provided with accessories such as hooks, wire rope slings, chain slings or textile slings. Please also refer to our description in the introduction to this section on lifting beams.

Код товара	WLL ton	Длина м	Width m	WLL т
13.356640KRTL050xxxzzz	0,5	1-6	1-6	-
13.356640KRTL010xxxzzz	1	1-6	1-6	-
13.356640KRTL020xxxzzz	2	1-6	1-6	-
13.356640KRTL030xxxzzz	3	1-6	1-6	-
13.356640KRTL040xxxzzz	4	1-6	1-6	-
13.356640KRTL050xxxzzz	5	1-6	1-6	-
13.356640KRTL060xxxzzz	6	1-6	1-6	-
13.356640KRTL080xxxzzz	8	1-6	1-6	-
13.356640KRTL100xxxzzz	10	1-6	1-6	-
13.356640KRTL120xxxzzz	12	1-6	1-6	-
13.356640KRTL150xxxzzz	15	1-6	1-6	-
13.356640KRTL200xxxzzz	20	1-6	1-6	-
13.356640KRTLyyyyxxxzzz	-	1-6	1-6	>20 Ton