

Flat Braided Wire Sling Powertex - FWS

Product information



The Powertex Flat Braided Wire Sling FWS is a flexible, cut-resistant steel wire lifting sling designed for controlled, stable load handling in industrial environments. It is manufactured from 10 galvanized 6x19M-WSC steel wire ropes braided together to create a flat lifting surface. This construction provides high flexibility combined with a wide contact area, helping distribute the load more evenly.

The FWS is suited for advanced lifting operations that require flexible yet cut-resistant slings. Each lot is break-tested before delivery and is fully traceable to its raw materials.

When to choose this product

- When you need a flexible steel wire sling that adapts well to loads
- When you want improved load contact compared to traditional round wire rope slings
- When your operation requires cut-resistant slings

It operates from -40°C to $+150^{\circ}\text{C}$, making it suitable for both cold outdoor sites and hot industrial environments.

Product Benefits

- **Flat braided construction made from 10 steel wire ropes**
Provides greater flexibility and a wider load contact surface than standard wire rope slings, helping improve load stability and reduce pressure points on the lifted object.
- **Made from robust and galvanized steel wire ropes**
The wire ropes offer higher safety against abrasion and cutting compared to textile slings. They also deliver predictable strength and durability, while galvanization helps protect against corrosion in everyday industrial environments.
- **Equipped with an aluminium conical ferrule with an inspection hole**
Conical ferrules prevent the sling from getting caught while the inspection hole allows for easy visual inspection. [... Read more](#)

Marking: CE-marked

Safety factor: 5:1

Flat Braided Wire Sling Powertex - FWS

Technical data

Код товара	Код	WLL ton	EWL m	WLL при петловом подъеме	WLL при U- подъеме 0°	WLL при U- подъеме 0°- 45°	WLL при U- подъеме 45°- 60°	Sling width mm	Вес kg
161500100100040	FWS0950	0,95	1	0,76	1,9	1,33	0,95	18	0,43
161500100200040	FWS0950	0,95	2	0,76	1,9	1,33	0,95	18	0,7
161500100300040	FWS0950	0,95	3	0,76	1,9	1,33	0,95	18	0,95
161500100400040	FWS0950	0,95	4	0,76	1,9	1,33	0,95	18	1,21
161500100500040	FWS0950	0,95	5	0,76	1,9	1,33	0,95	18	1,48
161500100600040	FWS0950	0,95	6	0,76	1,9	1,33	0,95	18	1,73
161500100800040	FWS0950	0,95	8	0,76	1,9	1,33	0,95	18	2,25
161500100XXX040	FWS0950	0,95	-	0,76	1,9	1,33	0,95	18	-
161500160100040	FWS1600	1,6	1	1,2	3,2	2,2	1,6	25	1,04
161500160200040	FWS1600	1,6	2	1,2	3,2	2,2	1,6	25	1,57
161500160300040	FWS1600	1,6	3	1,2	3,2	2,2	1,6	25	2,1
161500160400040	FWS1600	1,6	4	1,2	3,2	2,2	1,6	25	2,61
161500160500040	FWS1600	1,6	5	1,2	3,2	2,2	1,6	25	3,13
161500160600040	FWS1600	1,6	6	1,2	3,2	2,2	1,6	25	3,67
161500160800040	FWS1600	1,6	8	1,2	3,2	2,2	1,6	25	4,75
161500160XXX040	FWS1600	1,6	-	1,2	3,2	2,2	1,6	25	-
161500250100040	FWS2500	2,5	1	2	5	3,5	2,5	30	1,64
161500250200040	FWS2500	2,5	2	2	5	3,5	2,5	30	2,3
161500250300040	FWS2500	2,5	3	2	5	3,5	2,5	30	3
161500250400040	FWS2500	2,5	4	2	5	3,5	2,5	30	3,6
161500250500040	FWS2500	2,5	5	2	5	3,5	2,5	30	4,37
161500250600040	FWS2500	2,5	6	2	5	3,5	2,5	30	4,95
161500250800040	FWS2500	2,5	8	2	5	3,5	2,5	30	6,34
161500250XXX040	FWS2500	2,5	-	2	5	3,5	2,5	30	-
161500320120040	FWS3200	3,2	1,2	2,5	6,4	4,4	3,2	34	2,73
161500320200040	FWS3200	3,2	2	2,5	6,4	4,4	3,2	34	3,51
161500320300040	FWS3200	3,2	3	2,5	6,4	4,4	3,2	34	4,5
161500320400040	FWS3200	3,2	4	2,5	6,4	4,4	3,2	34	5,51
161500320500040	FWS3200	3,2	5	2,5	6,4	4,4	3,2	34	6,48
161500320600040	FWS3200	3,2	6	2,5	6,4	4,4	3,2	34	7,23
161500320800040	FWS3200	3,2	8	2,5	6,4	4,4	3,2	34	9,23

Flat Braided Wire Sling Powertex - FWS

Technical data

Код товара	Код	WLL ton	EWL m	WLL при петлевом подъеме	WLL при U- подъеме 0°	WLL при U- подъеме 0°- 45°	WLL при U- подъеме 45°- 60°	Sling width mm	Вес kg
161500320XXX040	FWS3200	3,2	-	2,5	6,4	4,4	3,2	34	-
161500480120040	FWS4800	4,8	1,2	3,8	9,6	6,7	4,8	42	2,8
161500480200040	FWS4800	4,8	2	3,8	9,6	6,7	4,8	42	4,2
161500480300040	FWS4800	4,8	3	3,8	9,6	6,7	4,8	42	5,6
161500480400040	FWS4800	4,8	4	3,8	9,6	6,7	4,8	42	7
161500480500040	FWS4800	4,8	5	3,8	9,6	6,7	4,8	42	8,4
161500480600040	FWS4800	4,8	6	3,8	9,6	6,7	4,8	42	9,8
161500480800040	FWS4800	4,8	8	3,8	9,6	6,7	4,8	42	12,6
161500480XXX040	FWS4800	4,8	-	3,8	9,6	6,7	4,8	42	-
161500580120040	FWS5800	5,8	1,2	4,6	11,6	8,1	5,8	46	3,8
161500580200040	FWS5800	5,8	2	4,6	11,6	8,1	5,8	46	5,7
161500580300040	FWS5800	5,8	3	4,6	11,6	8,1	5,8	46	7,6
161500580400040	FWS5800	5,8	4	4,6	11,6	8,1	5,8	46	9,5
161500580500040	FWS5800	5,8	5	4,6	11,6	8,1	5,8	46	11,4
161500580600040	FWS5800	5,8	6	4,6	11,6	8,1	5,8	46	13,3
161500580800040	FWS5800	5,8	8	4,6	11,6	8,1	5,8	46	17,1
161500580XXX040	FWS5800	5,8	-	4,6	11,6	8,1	5,8	46	-
161500800120040	FWS8000	8	1,2	6,4	16	11,2	8	58	5,6
161500800200040	FWS8000	8	2	6,4	16	11,2	8	58	8,8
161500800300040	FWS8000	8	3	6,4	16	11,2	8	58	12
161500800400040	FWS8000	8	4	6,4	16	11,2	8	58	15,2
161500800500040	FWS8000	8	5	6,4	16	11,2	8	58	18,4
161500800600040	FWS8000	8	6	6,4	16	11,2	8	58	21,6
161500800800040	FWS8000	8	8	6,4	16	11,2	8	58	28
161500800XXX040	FWS8000	8	-	6,4	16	11,2	8	58	-
161501100200040	FWS11000	11	2	8,8	22	15,4	11	65	15,8
161501100300040	FWS11000	11	3	8,8	22	15,4	11	65	19,7
161501100400040	FWS11000	11	4	8,8	22	15,4	11	65	23,6
161501100500040	FWS11000	11	5	8,8	22	15,4	11	65	27,5
161501100600040	FWS11000	11	6	8,8	22	15,4	11	65	31,4
161501100800040	FWS11000	11	8	8,8	22	15,4	11	65	39,2

Flat Braided Wire Sling Powertex - FWS

Technical data

Код товара	Код	WLL ton	EWL m	WLL при петлевом подъеме	WLL при U- подъеме 0°	WLL при U- подъеме 0°- 45°	WLL при U- подъеме 45°- 60°	Sling width mm	Вес kg
161501100XXX040	FWS11000	11	-	8,8	22	15,4	11	65	-