



Anchor Starcon Load Group 5,0 t

Product information

The Starcon spherical head anchor load group 5,0 t is a steel component made for concrete casting. The foot of the anchor is constructed especially for strong concrete anchorage.

The cylindrical head of the spherical anchor is attached to a Starcon Lifting eye, standard coupling lifting eye for lifting.

Starcon refers to the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

Marking: CE-marked, UKCA-marked

Код товара	Load grp.	Длина мм	Finish	D mm	D1 mm	D2 mm	L mm	Bec kg
99.101050650	5.0t	65	Untreated	20	36	50	65	0,32
99.101050652	5.0t	65	HDG	20	36	50	65	0,32
99.101050750	5.0t	75	Untreated	20	36	50	75	0,34
99.101050752	5.0t	75	HDG	20	36	50	75	0,34
99.101050850	5.0t	85	Untreated	20	36	50	85	0,36
99.101050852	5.0t	85	HDG	20	36	50	85	0,36
99.101050950	5.0t	95	Untreated	20	36	50	95	0,4
99.101050952	5.0t	95	HDG	20	36	50	95	0,4

99.101051100	5.0t	110	Untreated	20	36	50	110	0,43
99.101051102	5.0t	110	HDG	20	36	50	110	0,43
99.101051200	5.0t	120	Untreated	20	36	50	120	0,46
99.101051202	5.0t	120	HDG	20	36	50	120	0,46
99.101051400	5.0t	140	Untreated	20	36	50	140	0,49
99.101051402	5.0t	140	HDG	20	36	50	140	0,49
99.101051600	5.0t	160	Untreated	20	36	50	160	0,56
99.101051602	5.0t	160	HDG	20	36	50	160	0,56
99.101051800	5.0t	180	Untreated	20	36	50	180	0,61
99.101051802	5.0t	180	HDG	20	36	50	180	0,61
99.101052100	5.0t	210	Untreated	20	36	50	210	0,69
99.101052102	5.0t	210	HDG	20	36	50	210	0,69
99.101052400	5.0t	240	Untreated	20	36	50	240	0,76
99.101052402	5.0t	240	HDG	20	36	50	240	0,76
99.101053400	5.0t	340	Untreated	20	36	50	340	1,01
99.101053402	5.0t	340	HDG	20	36	50	340	1,01
99.101054800	5.0t	480	Untreated	20	36	50	480	1,36
99.101054802	5.0t	480	HDG	20	36	50	480	1,36

Blueprint

