

HAC H Aluminium Hydraulic Cylinder

Product information



Holmatro aluminum cylinders (HAC) -**S**pring or **H**ydraulic return

Unique specifications:

- Up to 50% lighter compared to steel cylinders - easy & ergonomic
- Duo power ring; a combination of a superior seal and an extremely strong composite bearing for a longer life span
- XL saddle optimally protects the plunger and guides the load as effectively as possible
- The plunger is coated with a hardened anodized layer, which makes it extremely wear & corrosion resistant

Standard supplied with:

- High flow female coupler A118
- Flat saddle
- Larger cylinders are equipped with handles for easy carrying and positioning


Also available:

- Tilting saddles
- Hydraulic pump units 700bar to control your system
- Hydraulic hoses 700bar
- System components to complete your hydraulic system

... [Read more](#)

HAC H Aluminium Hydraulic Cylinder

Blueprint



Technical data

Код товара	Код	WLL ton	stroke length mm	Closed height mm	required oil cc	Bec kg
5211100122086	HAC 30 H 5	30	50	197	166	6,9
5211100122085	HAC 30 H 10	30	100	247	332	8,5
5211100122080	HAC 30 H 15	30	150	297	497	10,2
5211100122095	HAC 50 H 5	50	50	201	192	9,5
5211100122108	HAC 50 H 10	50	100	251	385	11,5
5211100122097	HAC 50 H 15	50	150	301	577	13,3
5211100122094	HAC 100 H 5	100	50	246	433	19,7
5211100122109	HAC 100 H 10	100	100	296	865	23
5211100122107	HAC 100 H 15	100	150	346	1 298	26,8
5211100122075	HAC 150 H 5	150	50	248	613	27,7
5211100122074	HAC 150 H 10	150	100	298	1 227	32,3
5211100122073	HAC 150 H 15	150	150	348	1 840	38