

## Accessories - 15 - 50 Tons Cylinder

### Product information



Код товара	Description
45050005H	• Suitable for HGC 15 and HGC 25• Max. working pressure: 720 bar• Standard supplied with 2x bolt M12x30 and 2x bolt M10x30
45050004H	• Suitable for HGC 25 cylinders• Thread size: 2" NPT male - 1½"-16 UN male• Max. working pressure: 360 bar
45050194H	• To provide better grip• Suitable for HGC 25 and HCJ 25 cylinders• Thread size: 2" NPT female• Max. working pressure: 360 bar
45050002H	• Suitable for HGC 25 cylinders• Thread size: 2" NPT female• Max. working pressure: 360 bar• Standard supplied with 2x bolt M12x20
45050291H	• To mount on bottom side of cylinder• Suitable for HGC 25 and HCJ 25 cylinders• Thread size: 2" NPT female• Max. working pressure: 360 bar
45050218H	• To connect 2 extension tubes• Suitable for HGC 25 and HCJ 25 cylinders• Thread size: 2" NPT female (2x)• Max. working pressure: 360 bar
45050263H	• To connect accessories to cylinders• Suitable for HGC 25 and HCJ 25 cylinders• Thread size: 2" NPT male (2x)• Max. working pressure: 360 bar
45050341H	• Suitable for HGC 25 and HCJ 25 cylinders• Length: 250 mm• Thread size: 2" NPT male (2x)• Max. working pressure: 360 bar
45050343H	• Suitable for HGC 25 and HCJ 25 cylinders• Length: 500 mm• Thread size: 2" NPT male (2x)• Max. working pressure: 360 bar
45050345H	• Suitable for HGC 25 and HCJ 25 cylinders• Length: 750 mm• Thread size: 2" NPT male (2x)• Max. working pressure: 360 bar
45050005H	• Suitable for HGC 15 and HGC 25• Max. working pressure: 720 bar• Standard supplied with 2x bolt M12x30 and 2x bolt M10x30
45050174H	• Suitable for HCJ 25 cylinders• Thread size: 2" NPT female
45050241H	• Suitable for HCJ 25 cylinders• Thread size: 2" NPT male
45050237H	• Suitable for HGC 25 cylinders• Thread size: 3 5/16"-12 UN• Max. working pressure: 720 bar
45050285H	• Suitable for HCJ 25 cylinders• Thread size: M85x2• Max. working pressure: 720 bar
45050284H	• Suitable for HGC 50 cylinders• Thread size: 5"-12 UN• Max. working pressure: 720 bar