

## VARI Pump W D- 400V - 2 stage

### Product information



Holmatro VARI Pump units

**To control your hydraulic system, Holmatro offers a various range of pump units:**

- 230V, 400V or petrol driven
- 1 or 2 stage

**Unique specifications:**

- In case of a power failure, the oil pressure is maintained
- Protected against pressure drop by pressure-controlled non-return valve
- Excluding single-acting (M311) or double-acting (M322 or M323) control valve
- TIP: If you want to create flexibility for feature use; ad a Sada switch (M304) to your pump set-up

You want to make sure you choose the right vari-pump for your application? Download the Holmatro Vari pump configurator.

**Additional information:**

To have a safe and controlled system, assemble your vari-pump with advised components:

- Option A: 1 cylinder application : assemble a pressure gauge directly on the pump unit
- Option B: multiple cylinder application: add a flow panel & assembly set to your pump set-up
- TIP: download the vari-pump configurator for more info

**Why add a pressure gauge or flowpanel?**

- To measure the pressure in the system; safety first
- [Go here for the valves & accessories for Holmatro vari pumps](#)

[... Read more](#)

## VARI Pump W D- 400V - 2 stage

### Technical data

Код товара	Код	Max. working pressure bar/Mpa	oil capacity cc	Engine	Вес kg
5201100152064	12 W 25 E	720 / 72	25 000	400 VAC-1.5 kW-50 Hz-3 PH	64
5201100152065	12 W 50 E	720 / 72	50 000	400 VAC-1.5 kW-50 Hz-3 PH	94
5201100152067	18 W 25 E	720 / 72	25 000	400 VAC-2.2 kW-50 Hz-3 PH	96
5201100152068	18 W 50 E	720 / 72	50 000	400 VAC-2.2 kW-50 Hz-3 PH	96