



Lifting Eye Theipa Point - F

Product information

The eyes can be loaded with working load limit in all directions. All the eyes are pivoted to avoid breakage in the eyes, which also make it possible to fold it aside when it is not in use. Furthermore it has a ball beared sviwel which makes the lifting eye to always stand in the correct direction to the load.

The advantages:

- The stamped WLL applies to the kind of attachment by 90°.
- Bolts of the quality class 10.9 crack-tested are permitted as connecting elements
- **Different threaded versions and lengths can be supplied on request.**

Safety factor: 4:1

Код товара	Код	WLL ton	Thread mm	Tightening torque Nm	Pitch DIN 13	a mm	Ø b	b i	d mm	e mm	g mm	SW mm	t mm	t1 mm	Ø mm	Bec kg
11.420381800000	TP-F 0.5	0,5	M 12	15-40	1,75	45	36,5	32	M 12	15	73	34	66	55	13	0,61
11.420381801000	TP-F 1	1	M 16	45-130	2	52	36,5	32	M 16	20	80	34	73	55	13	0,65
11.420381802000	TP-F 1.7	1,7	M 20	100-170	2,5	66	52	34	M 20	25	106	46	95	70	16	1,5
11.420381804000	TP-F 2.1	2,1	M 24	190-280	3	80	57	45	M 24	30	120	50	108	85	18	2,12
11.420381806000	TP-F 3.2	3,2	M 30	230-400	3,5	94	70	46	M 30	40	148	65	131	86	20	3,7
11.420381808000	TP-F 5	5	M 36	270-600	4	107	80	60	M 36	45	164	75	145	115	23	5,75

Blueprint

