

## Lifting Eye FP

---

### Product information



The Flat Point is a rotatable attachment point with screw for lifting and load attachment applications. It is used where a low-profile lifting point is needed with defined WLL values and controlled load orientation.

#### Best used for:

- Machinery, tooling, and components requiring flat lifting points.
- Applications needing 360° rotation and 110° working range.

#### Product benefits:

- Flat design supports use where installation height is limited.
- Rotates 360° for easier alignment during lifting.
- Automatically locking link helps maintain controlled positioning.
- Crack-tested 10.9 screw supports documented lifting reliability.
- WLL range from 0.5 to 15 t supports load planning.

... [Read more](#)


---

**Marking:** CE-marked, UKCA-marked

**Safety factor:** 4:1

## Lifting Eye FP

### Blueprint



### Technical data

Код товара	Код	WLL ton	Thread	Torque Nm	A mm	B mm	C mm	Ø d mm mm	E mm	F mm	G mm	I mm	Øs mm mm	Вес kg
42150381100000	FP 0.5	0,5	M10	40	69	50	48	13	28	100	12	52	34	0,71
42150381101000	FP 0.8	0,8	M12	65	69	50	48	13	28	100	17	51	34	0,73
42150381101500	FP 1.5	1,5	M16	160	69	50	48	13	28	100	27	49	34	0,77
42150381102100	FP 2.5	2,5	M20	420	69	50	48	13	33	103	37	44	41	0,92
42150381104200	FP 4-S	4	M24	750	69	50	48	13	34	103	46	40	41	1,05
42150381104000	FP 4	4	M24	750	104	76	78	18	39	147	41	74	58	2,5
42150381105000	FP 5	5	M27	1 000	104	76	72	18	39	147	51	72	58	2,63
42150381106000	FP 6	6	M30	1 400	104	76	72	18	39	147	51	70	58	2,74
42150381108000	FP 8	8	M36	1 800	104	76	72	18	43	147	57	62	58	3,15