Lifting Solutions Group
Axel Johnson International

Horizontal Lifting Clamp IPH10(J)

Product information



The Crosby IP IPH10 / IPH10J horizontal lifting clamps are designed for lifting applications requiring paired clamps with defined working load limits and jaw openings. The welded alloy steel body provides strength in a compact design, while the IPH10J version accommodates thicker materials with its larger jaw opening. Available capacities and jaw openings allow selection according to the load and application requirements.

Best used for:

- Horizontal lifting operations using matched pairs of clamps.
- Applications requiring jaw openings up to 60 mm (IPH10) or 60–120 mm (IPH10J), depending on model.

Product benefits:

- Welded alloy steel body combines structural strength with compact dimensions.
- Spring-loaded tension, magnets and handle support positioning and handling on applicable models.
- Individual proof testing at twice the WLL provides documented load verification.
- Serialized clamps and included test certificates support traceability and inspection records.
- Available maintenance and repair kits support servicing and continued use

... *Read more*

Marking: According to standard, CE-marked
Standard: EN 13155


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Horizontal Lifting Clamp IPH10(J)

Blueprint



Technical data

Код товара	WLL ton	Jaw width mm	Model	A mm	B mm	C mm	E mm	F mm	G mm	H mm	J mm	K mm	L mm	Вес kg
502100050200170	0,5	0-20	0.5-IPH10*	0-20	86	12	16	103	150	60	12	27	4	1,8
502100100350170	1	0-35	1-IPH10*	0-35	100	16	16	103	150	60	12	31	7	2,5
502100200600170	2	0-60	2-IPH10	0-60	117	16	22	109	256	110	20	40	9	5,5
502100300600170	3	0-60	3-IPH10	0-60	117	20	26	109	266	120	20	48	11	7,5
502100301200170	3	60-120	3-IPH10J	60-120	177	20	26	109	266	120	20	48	11	9
502100450600170	4,5	0-60	4.5-IPH10	0-60	132	25	30	104	280	130	20	48	12	10,5
502100451200170	4,5	60-120	4.5-IPH10J	60-120	192	25	30	104	280	130	20	48	12	12
502100600600170	6	0-60	6-IPH10	0-60	143	25	36	123	320	130	20	48	14	13
502100601200170	6	60-120	6-IPH10J	60-120	203	25	36	123	320	130	20	48	14	15
502100900600170	9	0-60	9-IPH10	0-60	157	30	43	133	330	140	25	62	16	18,5
502100901200170	9	60-120	9-IPH10J	60-120	217	30	43	133	330	140	25	62	16	20,5
502101200600170	12	0-60	12-IPH10	0-60	172	30	47	141	353	150	25	62	17	21,5
502101201200170	12	60-120	12-IPH10J	60-120	232	30	47	141	353	150	25	62	17	24

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved