

Chain Sling Powertex 2-leg with Masterlink MC2 and Latch Hooks, Grade 10

Product information



The Chain Sling Powertex 2-leg MC-2 with latch hooks is a two-leg lifting assembly for general industrial use. It features an MC-2 master link with an integrated shortening function, reducing the number of components and creating a more compact and manageable lifting setup.

It is designed for controlled lifting where fast connection, quick length adjustment, and predictable performance are required.

The assembly includes the MC-2 master link, Grade 10 chain, latch hooks, and a marking plate with WLL information, providing a complete, ready-to-use configuration.

Best used for:

- Balanced lifting using two lifting points
- Applications where a compact setup with integrated shortening is preferred
- Repetitive lifting where fast and efficient hook connection improves handling speed

Product benefits

- MC-2 master link integrates shortening functions on both legs, reducing the number of components and simplifying assembly configuration
- Individual leg shortening allows quick length adjustment without adding separate shortening hooks
- Compact design supports a clearer overview during use and inspection, helping reduce handling errors
- Latch hook enables fast and secure attachment, reducing connection time during repetitive lifting operations
- Grade 10 chain provides higher capacity compared to Grade 8, enabling compact setups without increasing chain diameter

... [Read more](#)

Marking: According to standard, CE-marked

Standard: EN 818-4, AS 3776

(+25 % WLL)

Safety factor: 4:1

Класс: 10

Chain Sling Powertex 2-leg with Masterlink MC2 and Latch Hooks, Grade 10

Technical data

Код товара	Chain diameter mm	WLL ton	EWL m	WLL 0°-45° τ	WLL 45°-60° τ	Bec kg
240800600100230	6	2	1	2	1,4	2,84
240800600200230	6	2	2	2	1,4	4,44
240800600300230	6	2	3	2	1,4	6
240800600400230	6	2	4	2	1,4	7,6
240800600500230	6	2	5	2	1,4	9,2
240800600600230	6	2	6	2	1,4	10,8
240800600700230	6	2	7	2	1,4	12,4
240800600800230	6	2	8	2	1,4	14
240800800100230	8	3,55	1	3,55	2,5	5,3
240800800200230	8	3,55	2	3,55	2,5	8,3
240800800300230	8	3,55	3	3,55	2,5	11,3
240800800400230	8	3,55	4	3,55	2,5	14,3
240800800500230	8	3,55	5	3,55	2,5	17,3
240800800600230	8	3,55	6	3,55	2,5	20,3
240800800700230	8	3,55	7	3,55	2,5	23,3
240800800800230	8	3,55	8	3,55	2,5	26,3
240801000100230	10	5,6	1	5,6	4	9,4
240801000200230	10	5,6	2	5,6	4	14
240801000300230	10	5,6	3	5,6	4	18,6
240801000400230	10	5,6	4	5,6	4	23,2
240801000500230	10	5,6	5	5,6	4	27,8
240801000600230	10	5,6	6	5,6	4	32,4
240801000700230	10	5,6	7	5,6	4	37
240801000800230	10	5,6	8	5,6	4	41,6
240801300100230	13	9,5	1	9,5	6,7	15,7
240801300200230	13	9,5	2	9,5	6,7	23,5
240801300300230	13	9,5	3	9,5	6,7	31,3
240801300400230	13	9,5	4	9,5	6,7	39,1
240801300500230	13	9,5	5	9,5	6,7	47
240801300600230	13	9,5	6	9,5	6,7	54,7

Chain Sling Powertex 2-leg with Masterlink MC2 and Latch Hooks, Grade 10

Technical data

Код товара	Chain diameter mm	WLL ton	EWL m	WLL 0°-45° τ	WLL 45°-60° τ	Bec kg
240801300700230	13	9,5	7	9,5	6,7	62,5
240801300800230	13	9,5	8	9,5	6,7	70,3
240801600200230	16	14	2	14	10	36,3
240801600300230	16	14	3	14	10	47,9
240801600400230	16	14	4	14	10	59,5
240801600500230	16	14	5	14	10	71,1
240801600600230	16	14	6	14	10	82,7
240801600700230	16	14	7	14	10	94,3
240801600800230	16	14	8	14	10	105,9