

Chain Sling Powertex 2-leg with Masterlink MC2 and Safety Hooks, Grade 10

Product information



The Chain Sling Powertex 2-leg MC2 with safety hooks is a two-leg lifting assembly for general industrial use. It features an MC2 master link with integrated shortening functions on both legs, reducing the number of components and creating a more compact and manageable lifting setup.

It is designed for balanced lifting where load distribution, individual leg adjustment, and predictable performance are required.

The assembly includes the MC-2 Master Link, Grade 10 chain, safety hooks, and a marking plate with WLL information, providing a complete, ready-to-use configuration.

Best used for:

- Balanced lifting using two lifting points
- Applications where a compact setup with integrated shortening is preferred
- Lifting applications where secure hook closure is required to reduce the risk of unintentional release

Product Benefits

- MC-2 master link integrates the shortening function, reducing the number of components and simplifying assembly configuration
- Individual leg shortening allows accurate load balancing without adding separate shortening hooks
- Compact design supports a clearer overview during use and inspection, helping reduce handling errors
- Safety hooks provide secure closure, helping reduce the chance of unintentional hook release during lifting
- Grade 10 chain provides higher capacity compared to Grade 8, enabling compact setups without increasing chain diameter

... [Read more](#)

Marking: According to standard, CE-marked

Standard: EN 818-4, AS 3776

(+25 % WLL)

Safety factor: 4:1

Класс: 10

Chain Sling Powertex 2-leg with Masterlink MC2 and Safety Hooks, Grade 10

Technical data

Код товара	Chain diameter mm	WLL ton	EWL m	WLL 0°-45° τ	WLL 45°-60° τ	Bec kg
240800600100250	6	2	1	2	1,4	3,2
240800600200250	6	2	2	2	1,4	4,8
240800600300250	6	2	3	2	1,4	6,4
240800600400250	6	2	4	2	1,4	8
240800600500250	6	2	5	2	1,4	9,6
240800600600250	6	2	6	2	1,4	11,2
240800600700250	6	2	7	2	1,4	12,8
240800600800250	6	2	8	2	1,4	14,4
240800800100250	8	3,55	1	3,55	2,5	5,8
240800800200250	8	3,55	2	3,55	2,5	8,6
240800800300250	8	3,55	3	3,55	2,5	11,8
240800800400250	8	3,55	4	3,55	2,5	14,8
240800800500250	8	3,55	5	3,55	2,5	17,8
240800800600250	8	3,55	6	3,55	2,5	20,8
240800800700250	8	3,55	7	3,55	2,5	23,8
240800800800250	8	3,55	8	3,55	2,5	26,8
240801000100250	10	5,6	1	5,6	4	9,7
240801000200250	10	5,6	2	5,6	4	14,3
240801000300250	10	5,6	3	5,6	4	18,8
240801000400250	10	5,6	4	5,6	4	23,4
240801000500250	10	5,6	5	5,6	4	28
240801000600250	10	5,6	6	5,6	4	32,6
240801000700250	10	5,6	7	5,6	4	37,2
240801000800250	10	5,6	8	5,6	4	41,8
240801300100250	13	9,5	1	9,5	6,7	16,6
240801300200250	13	9,5	2	9,5	6,7	24,4
240801300300250	13	9,5	3	9,5	6,7	32,2
240801300400250	13	9,5	4	9,5	6,7	40
240801300500250	13	9,5	5	9,5	6,7	47,8
240801300600250	13	9,5	6	9,5	6,7	55,6

Chain Sling Powertex 2-leg with Masterlink MC2 and Safety Hooks, Grade 10

Technical data

Код товара	Chain diameter mm	WLL ton	EWL m	WLL 0°-45° τ	WLL 45°-60° τ	Bec kg
240801300700250	13	9,5	7	9,5	6,7	63,4
240801300800250	13	9,5	8	9,5	6,7	71,2
240801600200250	16	14	2	14	10	39
240801600300250	16	14	3	14	10	50,6
240801600400250	16	14	4	14	10	62,2
240801600500250	16	14	5	14	10	73,8
240801600600250	16	14	6	14	10	85,4
240801600700250	16	14	7	14	10	97
240801600800250	16	14	8	14	10	109