Lifting Solutions Group
Axel Johnson International

Wire rope Dyform Bristar 8

Інформація про товар



Dyform Bristar 8 is a high performance compacted single layer constructed rope which incorporates an engineered extruded plastic profile between the 8 outer strands and the rope core for cranes and industrial applications including mobile, crawler and tower cranes.

Standard: EN 12385-4
ISO 4309 Rope Category No: 10-17mm **RCN.04**, 18-34mm **RCN.09**, 36-50mm **RCN.11**

... *Read more*

Маркування: Згідно зі стандартом
Стандарт: EN 12385-4

Коефіцієнт заповнення: 0.68
RCN: 04

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Wire rope Dyform Bristar 8

Technical data

Код товару	Діаметр троса мм	Tensile strength N/mm²	Покриття	Rope lay	Мінімальна розривна сила кН 2160Н\мм2	Мастило	Вага kg/100m
103102804270659	28	1 960	Оцинковане	sZ	691	SupplierStandard	367
103103203270709	32	1 960	Оцинковане	zS	903	SupplierStandard	482
103103404270709	34	1 960	Оцинковане	sZ	1 020	SupplierStandard	544
103103604270709	36	1 960	Оцинковане	sZ	1 145	SupplierStandard	613
103103603270709	36	1 960	Оцинковане	zS	1 145	SupplierStandard	613
103103804270709	38	1 960	Оцинковане	sZ	1 300	SupplierStandard	685
103103803270709	38	1 960	Оцинковане	zS	1 300	SupplierStandard	685

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved