

## Wire Rope Clip with Forged Bridge Powertex PCTB

### Інформація про товар



The Powertex Wire Rope Clip with forged Bridge PCTB is suitable for suspending static loads and single-use lifting operations. Available in sizes from 6 to 40 mm, this wire rope clip is designed and tested in accordance with the EN 13411-5B standard, ensuring compliance and reliability in every use.

#### Product benefits

**Safety compliance:** These wire rope clips comply with EN 13411-5 (Type B) standards, meeting stringent safety and quality requirements.

**Superb grip:** The bridge features distinctive friction ridges that increase friction between the bridge and the wire rope, ensuring a secure grip where the rope makes contact with the bridge.

**High load capacity:** When correctly mounted, the assembly can withstand up to 80% of the rope's minimum breaking load (MBL), providing robust and reliable performance.

**Compatibility:** Designed for use with six-stranded right-hand lay ropes in 6x19 (M) and 6x36 classes and right-hand ordinary lay wire rope in 8x19 class up to 1960 N/mm<sup>2</sup>, with fiber core and steel core.


**Durable finish:** 7-10 mm Dacromet, >10 mm are hot-dip galvanized

**Full traceability:** Every Wire Rope Clip is marked with Powertex or PX branding, Size, and a traceability code, ensuring traceability to the production lot and raw materials.

[... Read more](#)

## Wire Rope Clip with Forged Bridge Powertex PCTB

### Креслення



### Technical data

Код товару	Код	Діаметр троса мм	Size	Thread	No. of clips when lifting	Torque Nm	A мм	C мм	D мм	F мм	G мм	H мм	I мм	J мм	Вага кг
121100700230	PCTB-7	6-7	1/4	5/16-18 UNC	2	20,3	38,5	16,4	19	30,7	19	7,4	18	28	0,08
121100800230	PCTB-8	8	5/16	3/8-16 UNC	3	40,7	43,2	20,5	22,6	33,3	22,6	9,2	21	37	0,12
121101000230	PCTB-10	9-10	3/8	7/16-14 UNC	3	61	49	22	25	40,3	25	10,7	25	39	0,2
121101100230	PCTB-11	11	7/16	1/2-13 UNC	3	88	58	28	30,5	47,3	30,5	12,1	26	50	0,32
121101300230	PCTB-13	12-13	1/2	1/2-13 UNC	3	88	58	28	30,5	47,3	30,5	12,1	26	51	0,33
121101500230	PCTB-15	14-15	9/16	9/16-12 UNC	3	129	63	31	34	51	34	14	38	63	0,45
121101600230	PCTB-16	16	5/8	9/16-12 UNC	3	129	63	31	34	51	34	14	38	64	0,46
121102000230	PCTB-20	18-20	3/4	5/8-11 UNC	4	176	72	34	39	57	39	15,4	42	73	0,65
121102200230	PCTB-22	22	7/8	3/4-10 UNC	4	305	80	36	44	62	44	18,7	44	79	0,94
121102600230	PCTB-26	24-26	1	3/4-10 UNC	5	305	88	44	47	66	47	18,7	52	93	1,1
121103000230	PCTB-30	28-30	1-1/8	3/4-10 UNC	6	305	90	48	51	69	51	18,7	54	99	1,3
121103400230	PCTB-34	32-34	1-1/4	7/8-9 UNC	7	488	104	53	58,2	78,5	58,5	21,2	58,5	111,5	1,8
121103600230	PCTB-36	36	1-3/8	7/8-9 UNC	7	488	105	56	59	80	59	21,2	61	118	2
121104000230	PCTB-40	38-40	1-1/2	7/8-9 UNC	8	488	112	60	66	86	66	21,2	62	124	2,3