
Lifting Solutions Group
Axel Johnson International

Steel Wire Rope Forest King

Інформація про товар



The most important advantage of ropes with such a construction construction is the excellent abrasion resistance of the outer surface of the rope and the significantly increased breaking strength of the rope, compared to the compared to a rope of standard design with, the same diameter. FOREST KING rope is proven ideal in the forest industry for skidding and timber transportation. ... *Read more*

Маркування: Згідно зі стандартом
Стандарт: EN 12385-4

Коефіцієнт заповнення: 0,657
RCN: 06
Відхилення Ø: 0% to +5%

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Steel Wire Rope Forest King

Technical data

Код товару	Діаметр троса мм	Tensile strength N/mm²	Покриття	Rope lay	Мінімальна розривна сила кН 2160Н\мм2	Мастило	Вага кг/м
103101004090990	10	2 060	Неоцинковане	sZ	104	Dry	0,57
103101104090990	11	2 060	Неоцинковане	sZ	123	Dry	0,7
103101204090990	12	2 060	Неоцинковане	sZ	144	Dry	0,83
103101304090990	13	2 060	Неоцинковане	sZ	165	Dry	0,98
103101404090990	14	2 060	Неоцинковане	sZ	188	Dry	1,15

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved